

An extreme range lubricant and anti-seize coating that withstands temperatures from -40°F to +600°F. Resists pressures up to 100,000 psi. Inert to water, oil, alkalis and many acids. Dry film coating will not attract dirt or dust. Contains pure Molybdenum Disulfide particles which burnish themselves into metal surfaces and provide a bonded lubricating film. Provides lubrication even under salt spray conditions.

**INDUSTRY USES:** Foundries, automotive plants, vehicle maintenance, sewing trades, paper and corrugated converting, chemical plants, textile plants, woodworking, marine, agricultural and military equipment, road equipment, oil drilling equipment, aircraft maintenance, steel mills, mining operations, etc.

**DIRECTIONS:** Shake can vigorously before application. Surface must be free from all loose rust, oil, grease and old paint. Spray with a sweeping motion, holding can 8 to 10 inches away from surface. Apply a thin uniform coating. Allow to set approximately 3 to 5 minutes before applying second coat.

**IMPORTANT:** To prevent clogging: After each use, invert can and spray a few short bursts to clear valve.

**DANGER:** Extremely Flammable Aerosol. Contains gas under pressure; May explode if heated. Causes skin and serious eye irritation. Suspected of causing cancer. May cause respiratory irritation, drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wear protective gloves and eye protection. Wash hands thoroughly after handling. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Avoid breathing mist, fumes, or spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Dispose of contents and container in accordance with local, state, and national regulations.

**WARNING:** This product can expose you to chemicals including Dichloromethane, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**CONTAINS (CAS#):** Methylene Chloride (75-09-2), Propane/n-Butane (68476-86-8), Isopropyl Alcohol (67-63-0), Molybdenum Disulfide (1317-33-5), Organophilic Clay (N/A).

**KEEP OUT OF REACH OF CHILDREN**  
For further information consult Safety Data Sheet

<b>HMS RATING:</b>	
HEALTH	3
FLAMMABILITY	3
REACTIVITY	1
PERSONAL	B




R12-22



# PATROL

## Dry Moly Lubricant



**Fast Dry / Oil Free**  
**Withstands Heavy Pressure**  
**and High Temperature**

**DANGER:**  
**EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS**  
**UNDER PRESSURE; MAY EXPLODE IF HEATED.**

NET WT. 12 OZ. (340 Grams)

**M-167**

**MID-AMERICAN RESEARCH CHEMICAL CORP.**  
**P.O. BOX 927 • COLUMBUS, NE 68602-0927**  
**800-228-8508**