

DISSOLVES:

**GREASE  
FAT  
SLIME**

## DIRECTIONS

Designed especially to dissolve grease and slime in lift stations, sewage treatment plants, cesspools, grease traps, drainage fields, and sludge aeration beds.

**LIFT STATIONS:** To be poured directly into manhole or lift station pit. If there is a heavy accumulation on side walls of manhole or lift station pit, **Citra-Clean Lift Station Maintainer** should be poured or sprayed through a MARC Pressure Sprayer (Hudson type) directly on side walls. **Citra-Clean Lift Station Maintainer** is a citrus-based product and will float on top of water. For best results it should be used in sufficient quantities to assure a 1 to 3 inch cap on the surface.

**FORMULA TO DETERMINE AMOUNT OF CITRA-CLEAN LIFT STATION MAINTAINER TO BE ADDED TO LIFT STATION:**

**ROUND LIFT STATION:** Diameter in FEET x Diameter in FEET ÷ 2 x Depth of Cap in INCHES = Gallons of **Citra-Clean Lift Station Maintainer** required.

**RECTANGULAR OR SQUARE LIFT STATION:** Length in FEET x Width in FEET x Depth of Cap in INCHES x .6 = Gallons of **Citra-Clean Lift Station Maintainer** required.

**SEPTIC TANKS - CESSPOOLS:** Add 1 pint per 500 gallon capacity for initial treatment. Use 1 to 2 oz. per week for each 500 gallon capacity as preventive maintenance treatment.

**DRAINS:** Pour one-half cup (4 oz.) of concentrate into drains. Allow to remain overnight, if possible -- at least two to four hours. **DO NOT ALLOW LIQUID OR VAPORS OF LIQUID TO COME IN CONTACT WITH FOOD.**

HMIS/NFPA Ratings: Health-2, Flammability-2, Reactivity-0.

**Net Contents: 5 Gallons**

**MARC** 

# **CITRA CLEAN** **LIFT STATION MAINTAINER**

**NATURAL CITRUS BASE**

- ★ **IMPROVES LIFT STATION EFFICIENCIES**
- ★ **ELIMINATES DOWN TIME**
- ★ **CONTROLS OBJECTIONABLE ODORS**
- ★ **EASY SOLUTION FOR DIRTY JOBS**



An Exclusive Formula Of **M-228**

**MID-AMERICAN RESEARCH CHEMICAL CORP.**  
P. O. BOX 927 · COLUMBUS, NE 68602-0927 · 800-228-8508

**TIME SAVER  
MONEY SAVER  
WORK SAVER  
READY-TO-USE  
BIODEGRADABLE  
ECONOMICAL**

## FEATURES

Dissolves fats and greases in catch basins, drain lines, etc.

Quickly dissolves grease and slime in septic tanks, cesspools, grease traps, drainage fields, and ditches. Controls bacterial odors with no harmful side effects to beneficial digestive organisms.

**DANGER:** Contains petroleum distillates and orange terpenes. Flammable liquid and vapor. May accumulate electrostatic charge and ignite and explode. May be fatal if swallowed and enters airways. Causes skin irritation. Suspected of causing cancer. May cause drowsiness or dizziness. Toxic to aquatic life with long-lasting effects. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks open flames and hot surfaces. No smoking. Keep container tightly closed. Ground container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist, vapors or spray. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye protection. Wash hands and any exposed skin thoroughly after handling. If exposed or concerned: Get medical attention. If on skin or hair: Take off immediately all contaminated clothing. Rinse skin and hair with water. If skin irritation occurs: Get medical attention. Wash contaminated clothing before reuse. If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a Poison Center or physician if you feel unwell. If swallowed: Immediately call a Poison Center or doctor. Do NOT induce vomiting. If case of fire: Use water spray, fog or regular foam for extinction. Collect spillage. Store locked up in a cool, well-ventilated place in a tightly closed container. Dispose of in accordance with federal, state and local regulations. **Keep Out of Reach of Children!** Made in USA. RM0715