



✓ STOPS
&
✓ PREVENTS

RUST

RUST-AWAY
RUST CONVERSION COATING

- INDUSTRIAL
- INSTITUTIONAL
- FARM • HOME

RUST-AWAY chemically alters existing rust into a PROTECTIVE POLYMERIC COATING on iron and steel.

Can be used as a primer for paint.

CAUTION: May cause irritation. Read carefully other cautions on back.

Net Contents: 16 fl. oz. (1 pt.)

An Exclusive Formula of **M-259**

MID-AMERICAN RESEARCH CHEMICAL CORP.
P. O. BOX 927 COLUMBUS, NE 68602-0927
800-228-8508

**IMPORTANT INFORMATION FOR
MAXIMUM SATISFACTION**

RUST-AWAY rust conversion coating chemically changes existing rust into a black protective polymeric coating and guards against formation of new rust. RUST-AWAY eliminates the need for sandblasting, grinding, scraping and sanding to bare metal. RUST-AWAY quickly and easily protects iron and steel.

No top coat is required if two coats of RUST-AWAY have been applied, however RUST-AWAY serves as a primer and can be overcoated with most paints after thoroughly drying. If a light top coat of paint is desired, use of a light colored primer will eliminate bleedthrough.

Fully dried and cured RUST-AWAY may be sanded before applying finish coat, and is compatible with all body fillers.

SHAKE OR STIR WELL before applying. Remove only loose or powdery rust, scale and deteriorated coatings. **Some rust is necessary for proper chemical reaction.** Thoroughly clean surface of dirt, salt, oil and grease. Test small area for compatibility.

Apply RUST-AWAY evenly by brush, spray or roller at the rate of approximately 500 sq. feet per gallon. Coating will dry to a darkened finish in 20 to 30 minutes. For increased protection, a second coat may be applied after the first coat has dried thoroughly. Maximum exposure resistance will develop in several days. Clean application equipment immediately with soap and water.

Note: Do not apply when the temperature is below 50° F. Apply only from a plastic container and do not return used product back to original container. Keep from freezing. Do not use on surfaces continually exposed to moisture or other liquids such as gasoline. No thinning is required.

Caution: Contains tannic acid and glycol ether. May cause irritation. May be harmful if swallowed. Avoid eye and skin contact. Do not take internally. In case of contact, flush thoroughly with water. Get medical attention if irritation persists. If swallowed, give several glasses of water or milk and call a physician immediately.

KEEP OUT OF REACH OF CHILDREN!

HMIS Ratings	Health	1	NFPA Ratings	
	Flammability	0		
	Reactivity	0		

VOC Content: 80 g/l



7 20302 25918 9
16 OZ RUST-AWAY

Buyer assumes responsibility for use, storage and disposal of product and container. We feel this product will perform exactly as represented. However, we have no control over the use or application thereof. We make no warranties, expressed or implied.

Made in USA

RM0414