

FEATURES

MARC SQUEAKY CLEAN is especially designed to clean wooden floors, particularly wooden gym floors. It removes dirt, oil, spills, perspiration, grime, etc. without harming the finish. When applied as directed, no rinsing of the floor is required.

Keeping a floor clean is one of the most important aspects of floor maintenance. Use of **MARC SQUEAKY CLEAN** in conjunction with frequent dust mopping will help reduce slipperiness and film formation, as well as enhance the finish.

MARC SQUEAKY CLEAN contains no ammonia, "butyl", chlorinated solvents or petroleum distillates.

DANGER: Contains isopropanol and nonylphenol ethoxylate. Flammable liquid and vapor. Causes eye irritation. May cause skin irritation. May be harmful if swallowed. Keep away from heat, sparks, open flames and other ignition sources. No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Wear protective gloves and eye protection. Avoid breathing vapors and mists. Wash skin thoroughly after handling. Use only in a well ventilated area. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If irritation persists, seek medical attention. IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation or rash occurs, seek medical advice. Wash contaminated clothing before reuse. If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF SWALLOWED: Call a POISON CENTER or seek medical advice if you feel unwell. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction. Store locked up in a cool, dry, well-ventilated area. Dispose of contents in accordance with all applicable local, regional and national regulations. **KEEP OUT OF REACH OF CHILDREN!**



SQUEAKY CLEAN

CONCENTRATED WOODEN FLOOR CLEANER



- ★ **REMOVES** DIRT, BODY OILS, SPILLS, PERSPIRATION
- ★ **REDUCES** SLIPPERINESS
- ★ **REDUCES** FILM FORMATION ON GYMS
- ★ **WILL NOT** HARM WOODEN FLOOR FINISHES
- ★ **CONTAINS** NO AMMONIA, "BUTYL", CHLORINATED SOLVENTS OR PETROLEUM DISTILLATES

An Exclusive Formula of

M-264

MID-AMERICAN RESEARCH CHEMICAL CORP.
P. O. BOX 927 • COLUMBUS, NE 68602-0927 • 800-228-8508

DIRECTIONS

MARC SQUEAKY CLEAN may be used with either a damp mop or as a tack towel application.

For tacking: Dust mop floor. Add 2 ounces of **MARC SQUEAKY CLEAN** per gallon of water. Saturate a towel with this solution and wring out as dry as possible. Place towel under a push broom or dust mop and push towel across floor. Rinse towel as required. No rinsing of the floor is needed.

NOTE: Use only for routine maintenance, not when sealing or finishing the floor. (When sealing or finishing, tack the floor with **MARC 234 "WOODY II"** for solvent-based finishes or just water with water-based finishes).

For use with a damp mop: Clean floor with dust mop. Make a solution of **MARC SQUEAKY CLEAN** at the rate of 2 ounces per gallon of water (use 4 ounces per gallon for very dirty floors). Damp mop floor. No rinsing is required. Allow floor to dry. Make up a fresh solution when solution is noticeably soiled to avoid redepositing dirt on floor.

HMIS Ratings	Health	0	NFPA Rating	
	Flammability	2		
	Reactivity	0		

Made in USA

Net Contents: 5 Gallons

RM0715