



INVERTED FLUORESCENT ORANGE SPRAY PAINT

Environmentally Formulated
Water-Base

V.O.C. COMPLIANT

NET WEIGHT 13.0 OUNCES (369 g)

WARNING! FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. See Other Cautions on Back/Side Panel.

M-849

MID-AMERICAN RESEARCH CHEMICAL CORP.
COLUMBUS, NE 68601

NON-CLOGGING EXCELLENT COVERAGE ON SOIL, GRASS, GRAVEL AND PAVEMENT

A heavy-duty, industrial paint with a water base formula that is fast drying, durable and non-clogging. Use in marking construction, excavation sites, underground utilities, landscaping, etc. Will not wash away or damage grass.

DIRECTIONS

1. For best results, use when can temperature is between 40°F and 90°F.
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Invert can and hold 4 to 6 inches above surface to be marked. Press sprayhead to the side to actuate.
4. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. DO NOT stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.
5. To clear sprayhead for future use, turn can right side up and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

Contains: VM&P Naphtha 64742-89-8, Calcium Carbonate 1317-65-3, Propane 74-98-6, N-Butane 106-97-8, Isobutyl Acetate 110-19-0, Mineral Spirits 64742-47-8. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120°F.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. OTHER INGREDIENTS: "Contents Partially Unknown", Water 7732-18-5, V.T. Alkyd Resin 71243-64-6.

Vapors may ignite explosively. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening windows and doors to achieve cross-ventilation.

Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA approved) or leave the area. Avoid contact with eyes, skin and clothing.

First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water.

KEEP OUT OF REACH OF CHILDREN

Ground Traffic Marking Coatings Do Not Exceed 66% VOC or 1.20 MIR

R 10-97
RM09-06