# SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER AND NAME: MARC 228-PT PINE CLEANER LIFT STATION MAINTAINER PT

SDS DATE: 12/28/2018

SUPPLIER: Mid-American Research Chemical Corp. ADDRESS: P. O. Box 927 Columbus, NE 68602-0927

PHONE: 402-564-7104 FAX: 403-563-1290 EMERGENCY PHONE: InfoTrac 1-800-535-5053

E-MAIL: marc@marc1.com WEBSITE: www.marc1.com

RECOMMENDED USE: Lift station treatment.

PREPARED BY: MARC

# **SECTION 2: HAZARDS IDENTIFICATION**

CLASSIFICATION: FLAMMABLE LIQUIDS - Category 3, ACUTE TOXICITY: INHALATION - Category 4, SKIN CORROSION/IRRITATION - Category 2, SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A, CARCINOGENICITY - Category 2, SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Narcotic effects] - Category 3, SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) [central nervous system (CNS)] - Category 2, ASPIRATION HAZARD - Category 1

SIGNAL WORD AND PRECAUTIONARY STATEMENTS-- DANGER: Contains petroleum distillates and dipentene. Flammable liquid and vapor. May accumulate electrostatic charge and ignite and explode. May be fatal if swallowed and enters airways. Causes skin irritation. Suspected of causing cancer. May cause drowsiness or dizziness. Toxic to aquatic life with long-lasting effects. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks open flames and hot surfaces. No smoking. Keep container tightly closed. Ground container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist, vapors or spray. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye protection. Wash hands and any exposed skin thoroughly after handling. If exposed or concerned: Get medical attention. If on skin or hair: Take off immediately all contaminated clothing. Rinse skin and hair with water. If skin irritation occurs: Get medical attention. Wash contaminated clothing before reuse. If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a Poison Center or physician if you feel unwell. If swallowed: Immediately call a Poison Center or doctor. Do NOT induce vomiting. If case of fire: Use water spray, fog or regular foam for extinction. Collect spillage. Store locked up in a cool, well-ventilated place in a tightly closed container. Dispose of in accordance with federal, state and local regulations.







# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

 INGREDIENT
 CAS NO.
 %

 Petroleum Distillate
 8052-41-3
 40-60

 Dipentene
 68956-56-9
 40-60

Percentage of composition has been withheld as a trade secret.

## **SECTION 4: FIRST AID MEASURES**

**EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If concerned, get medical advice/attention or call a POISON CENTER if irritation develops or persists and you feel unwell.

SKIN (or hair): Take off immediately all contaminated clothing. Wash off with soap and plenty of water. In case of eczema or other skin

disorders, or if rash occurs, seek medical advice/attention. Wash contaminated clothing before reuse.

INGESTION: Rinse mouth. If swallowed, seek medical advice immediately and show this container or label.

INHALATION: Remove to person to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if

needed. Call a POISON CENTER or doctor/physician if you feel unwell.

# MOST IMPORTANT SYMPTOMS/

**EFFECTS, ACUTE & DELAYED:** May cause drowsiness and dizziness, headache, nausea, vomiting. Exposed individuals may experience eye tearing, redness, and discomfort. Irritation of eyes and mucous membranes. Irritation of nose and throat. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

#### INDICATION OF IMMEDIATE MEDICAL

**ATTENTION & SPECIAL TREATMENT NEEDED**: Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

**GENERAL INFORMATION:** Take off all contaminated clothing immediately. If exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

#### **SECTION 5: FIRE FIGHTING MEASURES**

**EXTINGUISHING MEDIA:** Water fog, foam, dry chemical powder, carbon dioxide (CO2).

UNSUITABLE EXTINGUISHING MEDIA: Do not use water jet as an extinguisher, as this will spread the fire.

SPECIAL FIRE FIGHTING PROCEDURES

FIRE-FIGHTING EQUIPMENT:

In case of fire and /or explosion do not breathe fumes. A self-contained breathing apparatus and full protective clothing must be worn. Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if

you can do so without risk.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid and vapor. Vapors may form explosive mixtures with air. Vapors may

travel considerable distance to a source of ignition and flash back. During fire, gases

hazardous to health may be formed.

HAZARDOUS DECOMPOSITION PRODUCTS: No hazardous decomposition products are known.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES/ PROTECTIVE EQUIPMENT: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate personal protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 if SDS.

**METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP:** Refer to attached safety data sheets and/or instructions for use. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Never return spills to original containers for re-use. For waste disposal, see Section 13 of the SDS.

**ENVIRONMENTAL PRECAUTIONS:** Avoid discharge into drains, water courses or onto the ground.

# **SECTION 7: HANDLING AND STORAGE**

PRECAUTIONS FOR

SAFE HANDLING: Obtain special instructions before use. Do not handle until all safety precautions have been read and

understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective

equipment. Wash hands thoroughly after handling. Observe good hygiene practices.

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN! READ LABEL CAREFULLY!

Store locked up. Keep away from heat, sparks and open flame. Store in cool, dry place out of direct sunlight.

Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible

materials (see Section 10 of SDS).

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limits-Petroleum Distillates** 

......

Petroleum Distillate (CAS 8052-41-3)

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

COMPONENTS	TYPE	VALUE
Petroleum Distillate (CAS 8052-41-3)	PEL	100 ppm 2900 mg/m3
US. ACGIH Threshold Limit Values		
COMPONENTS	TYPE	VALUE
Detroloure Distillate (CAC 0052 44 2)	TIMA	400 mm
Petroleum Distillate (CAS 8052-41-3)	TWA	100 ppm
US. NIOSH: Pocket Guide to Chemical Hazards		
COMPONENTS	TYPE	VALUE

1800 mg/m3

350 mg/m3

**APPROPRIATE ENGINEERING CONTROLS:** Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**VENTILATION:** Explosion-proof general and local exhaust ventilation.

Ceiling

TWA

RESPIRATORY PROTECTION: If engineering controls do not maintain airborne concentrations below recommended exposure limits,

an approved respirator must be worn – a chemical respirator with organic vapor cartridge.

**EYE/FACE PROTECTION:** Chemical splash goggles where there is a potential for eye contact.

**SKIN PROTECTION/PROTECTIVE GLOVES:** Wear appropriate chemical resistant gloves.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Wear suitable protective clothing and gloves.

WORK HYGIENIC PRACTICES: When using, do not eat, drink or smoke. Always observe good personal hygiene measures,

such as washing after handling the material and before eating, drinking, and/or smoking. Routinely

wash work clothing and protective equipment to remove contaminants.

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE:

PHYSICAL STATE: Liquid.
COLOR: Clear liquid.
ODOR: Pine
ODOR THRESHOLD: Not available.

pH: Not available.

MELTING/FREEZING POINT: Not applicable/ Not available.

INITIAL BOILING POINT/RANGE: 310°F

FLASH POINT/METHOD USED: 110.0°F (TCC)
EVAPORATION RATE: >1 Ethyl ether = 1

FLAMMABILITY (solid, gas): Not available

**UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:** 

Explosive limit - lower:
Explosive limit - upper:
VAPOR PRESSURE (mmHg):
VAPOR DENSITY (AIR = 1):

Not available
Not determined
Not determined

RELATIVE DENSITY: 0.82

SPECIFIC GRAVITY (H2O = 1): Not available SOLUBILITY IN WATER: Negligible PARTITION COEFFICIENT,

n-OCTANOL/WATER: Not available
AUTO-IGNITION TEMPERATURE: Not available
DECOMPOSITION TEMPERATURE: Not available
VISCOSITY: Not available

OTHER INFORMATION

**DENSITY:** 6.8 lbs./gal.

#### **SECTION 10: STABILITY AND REACTIVITY**

**REACTIVITY:** The product is stable and non-reactive under normal conditions of use, storage and transport.

**CHEMICAL STABILITY:** Material is stable under normal conditions.

**POSSIBILITY OF HAZARDOUS** 

**REACTIONS:** No dangerous reaction known under conditions of normal use.

**CONDITIONS TO AVOID:** Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point.

Contact with incompatible materials.

INCOMPATIBILITY (MATERIAL TO AVOID): Strong acids. Strong oxidizing agents. Halogens.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: No hazardous decomposition products are known.

HAZARDOUS POLYMERIZATION: N/A CONDITIONS TO AVOID (POLYMERIZATION): NA

# SECTION 11: TOXICOLOGICAL INFORMATION

#### INFORMATION ON LIKELY ROUTES OF EXPOSURE:

EYES: Causes eye irritation. Symptoms may include stinging, tearing, redness, swelling and blurred vision.

**SKIN:** Causes skin irritation. May cause an allergic skin reaction.

**INGESTION:** Expected to be a low ingestion hazard.

INHALATION: Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause

Drowsiness and dizziness, headache, nausea and vomiting.

## SYMPTOMS RELATED TO THE

PHYSICAL, CHEMICAL AND

**TOXICOLOGICAL CHARACTERISTICS**: May cause drowsiness and dizziness, headache, nausea, vomiting. Irritation of eyes and mucous membranes. Exposed individuals may experience eye tearing, redness, and discomfort. Irritation of nose and throat. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

#### **INFORMATION ON TOXICOLOGICAL EFFECTS:**

**ACUTE TOXICITY:** Harmful if inhaled. Narcotic effects. May cause an allergic skin reaction.

# Petroleum Distllates LD50 / LC50:

Inhalation LC50 Rat >5 mg/L (4Hr mist)
Oral LD50 Rat >5000 mg/kg
Dermal LD50 Rabbit >2000 mg/kg

Skin corrosion/irritation: Causes skin irritation.
Serious eye damage/eye irritation: Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization:

Skin sensitization:

Not a respiratory sensitizer.

May cause an allergic skin reaction.

Carcinogenicity: May cause cancer.

**Specific target organ toxicity-** May cause drowsiness and dizziness.

Single exposure:



Product: MARC 228-PT PINE CLEANER LIFT STATION MAINTAINER PT

Form R04132

Specific target organ toxicity-

Repeated exposure: Chronic effects: Causes damage to organs through prolonged or repeated exposure.

Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may

be harmful. Prolonged exposure may cause chronic effects.

# SECTION 12: ECOLOGICAL INFORMATION

# Petroleum Distillate Component Analysis- Ecotoxicity - Aquatic Life Duration/Test/Species Concentration/Conditions

96 hrs. LL50 Oncorhyncus mykiss 8.2 mg/L 48 hrs. EL50 Oncorhyncus mykiss 32 mg/L 96 hrs. EL50 Scenedesmus subspicatus 45 mg/L

Chronic Survival NOELR

Aquatic Vertebrates 2.6 mg/L

Chronic Growth NOELR

Aquatic Vertebrates 2.6 mg/L Chronic Survival NOELR

Daphnia magna Chronic Reproduction EL 50

Daphnia magna 10 mg/L

Chronic reproduction NOELR

Daphnia magna 2.6 mg/L

Persistence & Degradability Inherently biodegradable

Bioaccumulation Potential Not Available Soil Mobility Not Available Other Adverse Effects Not Available

## **SECTION 13: DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL METHOD:** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

16 mg/L

LOCAL DISPOSAL REGULATIONS: Dispose in accordance with all applicable regulations.

HAZARDOUS WASTE CODE: The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

**WASTE FROM RESIDUES/** 

UNUSED PRODUCTS:

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see

Disposal instructions).

**CONTAMINATED PACKAGING:** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container

is emptied.

# **SECTION 14: TRANSPORT INFORMATION**

# U.S. DEPARTMENT OF TRANSPORTATION (for ground/non-bulk containers)

CONTAINER SIZES(S): PAILS PROPER SHIPPING NAME: COMPOUND, CLEANING, LIQUID

HAZARD CLASS: N/A
ID NUMBER: NONE
PACKING GROUP: NONE
LABEL STATEMENT: NONE

# **SECTION 15: REGULATORY INFORMATION**

U.S. FEDERAL REGULATIONS: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard,

29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA (TOXIC SUBSTANCE CONTROL ACT): Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

SARA 304 EMERGENCY RELEASE NOTIFICATION: Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA)

Hazard categories Immediate Hazard – Yes

Delayed Hazard – Yes Fire Hazard – Yes Pressure Hazard – No Reactivity Hazard – No

SARA 302 extremely hazardous substance: Not listed.

SARA 311/312 Hazardous chemical: No

SARA 313 (TRI reporting)

Safe Drinking Water Act

Not regulated.

(SDWA)

#### **SECTION 16: OTHER INFORMATION**

HMIS/NFPA Ratings: Health = 2

Flammability = 2
Reactivity = 0
Other = Protection = -

**REVISION DATE:** 12/28/2018

N/A = Not Applicable, N/D = Not Determined, N/E = Not Established

DISCLAIMER: While the information contained herein is believed to be correct, no warranties are made with respect thereto, and all liability from reliance thereon is disclaimed.