

Vinyl Tile Sealed Wood
Asphalt Tile Resilient Tile
Linoleum Sealed Terrazzo

FEATURES

MARC White Lightning is a high gloss, high durability, premium metal-crosslinked floor finish. It is specially designed to withstand daily high speed burnishing with electric or propane buffers without excessive powdering or wear. It may also be maintained on a low speed program or only buffed intermittently.

MARC White Lightning has excellent scuff and black mark resistance.

STRIPPING

MARC White Lightning can be effectively removed with MARC 39 Plus Super Strip, MARC 75 Easy Strip or MARC 272 Once Over.

WARNING: Contains polyethylene glycol mono (p-nonylphenyl) ether and glycol ether. Causes serious eye irritation. Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves and eye protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If on skin: Wash off thoroughly with water. Do not take internally. Use with adequate ventilation. Keep container closed when not in use. **KEEP OUT OF REACH OF CHILDREN! KEEP FROM FREEZING.**

HMIS/NFPA Ratings:
Health-0, Flammability-0,
Reactivity-0.



WHITE LIGHTNING HIGH SPEED FLOOR FINISH

- ★ High Gloss
- ★ High Durability
- ★ Excellent Response to Buffing

Coverage: 2,000 to 2,500 square feet per gallon.

Drying Time: 30 to 60 minutes under normal conditions.

An Exclusive Formula of **M-42**

MID-AMERICAN RESEARCH CHEMICAL CORP.
P. O. BOX 927 · COLUMBUS, NE 68602-0927 · 800-228-8508

Detergent Resistant
Self-Leveling
Will Not Yellow
Scuff and Mark Resistant
Non-Streaking
Slip Retardant

DIRECTIONS

Mop or strip floor as needed. Floor should be thoroughly clean and dry. For best results after deep stripping, first apply a sealer such as MARC 235 Sealer. Apply **MARC White Lightning** in even coats up to 2,500 square feet per gallon using a clean mop or lamb's wool applicator. Apply two to three coats for maximum gloss. After deep stripping, four to five coats may be applied; allow extra drying time.

For best results from burnishing, the application of five coats of **MARC White Lightning** finish is recommended.

Allow 30 to 60 minutes between the first and second coats during low humidity, and longer times between subsequent coats. When humidity is high (70% or above), allow as long as several hours before recoating.

To maintain appearance, floor may be buffed at regular speed or, for optimum appearance, burnished using high or ultra-high speed buffing machines. Clean floor thoroughly before buffing with a neutral floor cleaner such as MARC 239 Renew.

Net Contents: 5 Gallons

RM0515