

**Vinyl Tile    Asphalt Tile**  
**Resilient Tile**  
**Linoleum    Sealed Terrazzo**

#### FEATURES

**MARC White Lightning** is a high gloss, high durability, premium metal-crosslinked floor finish. It is specially designed to withstand daily high speed burnishing with electric or propane buffers without excessive powdering or wear. It may also be maintained on a low speed program or only buffed intermittently.

**MARC White Lightning** has excellent scuff and black mark resistance.

#### STRIPPING

**MARC White Lightning** can be effectively removed with MARC 39 Plus Super Strip or MARC 272 Once Over.

**WARNING:** Contains polyethylene glycol mono (p-nonylphenyl) ether and glycol ether. Causes serious eye irritation. Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves and eye protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If on skin: Wash off thoroughly with water. Do not take internally. Use with adequate ventilation. Keep container closed when not in use. **KEEP OUT OF REACH OF CHILDREN! KEEP FROM FREEZING.**

HMIS/NFPA Ratings:  
Health-0, Flammability-0,  
Reactivity-0.



**MARC** 

# WHITE LIGHTNING HIGH SPEED FLOOR FINISH

- ★ High Gloss
- ★ High Durability
- ★ Excellent Response to Buffing

**Coverage: 2,000 to 2,500 square feet per gallon.**

**Drying Time: 30 to 60 minutes under normal conditions.**

An Exclusive Formula of **M-42**

MID-AMERICAN RESEARCH CHEMICAL CORP.  
P. O. BOX 927 · COLUMBUS, NE 68602-0927 · 800-228-8508

**Detergent Resistant**  
**Self-Leveling**  
**Will Not Yellow**  
**Scuff and Mark Resistant**  
**Non-Streaking**  
**Slip Retardant**

#### DIRECTIONS

Mop or strip floor as needed. Floor should be thoroughly clean and dry. For best results after deep stripping, first apply a sealer such as MARC 235 Sealer. Apply **MARC White Lightning** in even coats up to 2,500 square feet per gallon using a clean mop or lamb's wool applicator. Apply two to three coats for maximum gloss. After deep stripping, four to five coats may be applied; allow extra drying time.

For best results from burnishing, the application of five coats of **MARC White Lightning** finish is recommended.

Allow 30 to 60 minutes between the first and second coats during low humidity, and longer times between subsequent coats. When humidity is high (70% or above), allow as long as several hours before recoating.

To maintain appearance, floor may be buffed at regular speed or, for optimum appearance, burnished using high or ultra-high speed buffing machines. Clean floor thoroughly before buffing with a neutral floor cleaner such as MARC 239 Renew.

**Net Contents: 5 Gallons**

R1020