

- ★ **SUPER HI-HEAT FORMULA**
- ★ **FAST-ACTING**
- ★ **NON-COMBUSTIBLE**

DESCRIPTION

MARC FIREBALL SEWER SOLVENT is excellent to use for preventing and relieving plugged sewer lines due to tree roots, detergent caking, grease, organic waste and sewer sludge.

Frozen sewer lines should be treated with **MARC FIREBALL SEWER SOLVENT** by using the same quantities as recommended for clogged lines, except that the product should be added gradually.

As a preventative, use **MARC FIREBALL SEWER SOLVENT** monthly. The normal preventative dosage is 1/4 of the quantity recommended for clogged lines.

If for any reason a mechanical rodding device is used, it should be followed by a treatment of **MARC FIREBALL SEWER SOLVENT** and flushing. Then, begin a regular preventative maintenance program to avoid future clogging.

MARC FIREBALL SEWER SOLVENT is a must in Municipalities, Dairies, Meat Processing Plants, Food Plants, Golf Courses, etc.

**KEEP OUT OF REACH OF CHILDREN!
FOR MUNICIPAL AND INDUSTRIAL USE ONLY!**

Made in USA 



FIREBALL



SEWER SOLVENT



Danger

May be corrosive to metals. May intensify fire. Oxidizer. Causes severe skin burns and eye damage. Harmful to aquatic life.

Contains: Sodium hydroxide, Sodium nitrate, and Aluminum.

Prevention: Keep away from flammable, combustible and reducing materials. Keep only in original container tightly closed. Use in well-ventilated area. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves, protective clothing and eye protection and face protection. Avoid breathing dust or mist. Avoid release to the environment. **Response:** In case of fire: Consider carbon dioxide, dry chemical, dry sand or alcohol-resistant foam to extinguish. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation occurs. **IF ON SKIN:** Take off contaminated clothing and wash before reuse. Wash with plenty of soap and water. If irritation occurs get medical advice/attention. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call POISON CENTER/doctor if you feel unwell. **IF SWALLOWED:** Do not induce vomiting. Rinse mouth. Call a POISON CENTER or doctor/physician if you feel unwell. **Storage:** Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Store in a corrosive-resistant container. **Disposal:** Dispose of contents/container to an approved waste treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. **FOR PROFESSIONAL USE ONLY. KEEP OUT OF REACH OF CHILDREN. REFER TO SDS FOR MORE INFORMATION.**

An Exclusive Formula of

M-59

MID-AMERICAN RESEARCH CHEMICAL CORP.
P. O. BOX 927 · COLUMBUS, NE 68602-0927 · 800-228-8508

- ★ **WILL NOT HARDEN**
- ★ **PREVENTS CLOGGING**
- ★ **COLOR CODED**
- ★ **READY-TO-USE**


DIRECTIONS

For clogged sewers, use 1 pound for each 15 feet of length and 2 inches of pipe diameter. For example:

Pipe Diameter	Amount for each 15 feet of Pipe Length
2"	1 lb.
4"	2 lbs.
8"	4 lbs.
12"	6 lbs.

Whenever possible, it is advantageous to block the line to allow **MARC FIREBALL SEWER SOLVENT** to remain in contact with the obstruction for as long as possible. Ask your MARC representative for suggestions on how to block lines.

When used as recommended, **MARC FIREBALL SEWER SOLVENT** will not adversely affect septic tanks, cesspools or sewage treatment plants. In fact, it can be used to dissolve accumulations of grease and sludge. Excellent for cleaning lift stations. Use one pail for every five feet of diameter.

HMIS Ratings	Health	3	NFPA Rating	
	Flammability	1		
	Reactivity	3		

Net Wt. 50 lbs.

RM0715