

MARCO



FORCE



ODOR SUPPRESSANT

HIGHLY CONCENTRATED - INDUSTRIAL GRADE
TROPICAL-CITRUS FRAGRANCE

Designed for:

- Institutions • Waste Treatment Plants •
- Drains • Vehicles •

Controls Odors From:

- Hospitals • Sewage • Drains •
- Restrooms • Garbage •

Net Contents: 32 fl. oz. (1 qt.) 946 ml

An Exclusive Formula of M-63

MID-AMERICAN RESEARCH CHEMICAL CORP.
P. O. BOX 927 · COLUMBUS, NE 68602-0927 · 800-228-8508

FEATURES

FORCE is a highly concentrated odor suppressant which counteracts even the most hard-to-control odors in schools, hospitals, nursing homes, sewage treatment plants, drains, grease traps, septic tanks, restrooms, locker rooms and garbage areas. Simply spray or pour **FORCE** onto the source of the problem, or spray into the air. **FORCE** will not adversely affect bacterial action in treatment plants or drains. It is non-combustible.

WARNING: Contains nonionic emulsifier. Causes eye irritation. Wash thoroughly after handling. Use with adequate ventilation. Do not spray in eyes or on skin. Wear safety glasses and rubber gloves when using. Do not breathe vapors directly. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention. If on skin: Wash off thoroughly with water. If skin irritation persists: Get medical attention. Store in a cool, well ventilated area. **KEEP OUT OF REACH OF CHILDREN!**

DIRECTIONS FOR USE

Spray **FORCE** onto odor-causing areas: Around toilets, urinals, storage bins, lockers and floor drains. This is not a substitute for cleaning, but will help to control odors until cleanup is possible.

Spray **FORCE** into and around garbage bins, pails and dumpsters.

To control odors in the air, spray a fine mist of **FORCE** into the air.

To deodorize carpeting, add four ounces of **FORCE** per gallon of water to the solution tank of a carpet extractor along with the regular cleaning product, and clean carpet as usual.

To control odors in drains and grease traps, pour two to six ounces of **FORCE** into drain. For sewage treatment plants, spray **FORCE** directly onto odor causing material, or add at the rate of several parts per million, as required.

RM0216