

DESIGNED FOR

**Sanitary Sewers
Storm Sewers
Lift Stations
Grease Traps
Sewage Treatment Plants
Packing Houses
Shower Drains**


FEATURES

A polyelectrolytic chemical specially formulated to change the natural character of organic and inorganic deposits by reducing their adhesive force. (It will reduce the adhesive force that bonds materials to one-ten thousandth of its original strength). In so doing this will allow any water flow of at least 2 to 3 gallons per minute to carry the deposits away.

SAND & SILT FLUSH is a biodegradable chemical that is non-toxic, non-corrosive, non-caustic. Being a completely safe chemical, SAND & SILT FLUSH will not adversely affect the B.O.D. or bacterial action in a Sewage Plant or Sewage Lagoon.

USAGE

SAND & SILT FLUSH is effective at dosage rates ranging from 1 quart to 3 gallons per 1000 gallons of flushing water. One gallon of SAND & SILT FLUSH will remove as much as 1 ton of mud from sanitary and storm sewers. One quart will usually treat 100 to 150 feet of 12 inch diameter sewer lines.

HMIS Ratings	Health	0	NFPA Ratings	
	Flammability	0		
	Reactivity	0		

Net Contents _____



SAND & SILT FLUSH

**FOR TREATMENT OF
ORGANIC AND INORGANIC
MATERIALS SUCH AS MUD,
DIRT, SILT, SLUDGE**

- **SAFE**
- **HIGHLY CONCENTRATED**
- **ECONOMICAL**
- **FAST**
- **BIODEGRADABLE**

WARNING: Contains acrylic polymers and isopropanol. Causes eye irritation. May cause skin irritation. May be harmful if swallowed. Wear protective gloves and eye protection. Avoid breathing mists. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If irritation persists, seek medical attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs, seek medical advice. Wash contaminated clothing before reuse. IF SWALLOWED: Call a POISON CENTER or seek medical advice if you feel unwell. Store in a cool, dry, well-ventilated area. Dispose of contents in accordance with all applicable local, regional and national regulations. Do not mix with acids, alkalis or any other chemicals. **KEEP OUT OF REACH OF CHILDREN!**



AN EXCLUSIVE FORMULA OF

M-67

MID-AMERICAN RESEARCH CHEMICAL CORP.
P. O. BOX 927 · COLUMBUS, NE 68602-0927 · 800-228-8508

DESIGNED FOR

**Swimming Pools
Industrial Plants
Automotive Dealers
Bus Garages
Auto Wash
Street Sweepers & Washers**

SPRING OR FALL FLUSHING USAGE

When using a fire hose, add SAND & SILT FLUSH at the rate of 2 to 3 gallons per 1000 gallons of flushing water. Estimate water flow by timing. User can also add SAND & SILT FLUSH By using a ratio of 1 gallon per 100 feet of 12 inch diameter sewer lines.

When using hydraulic jet pumping unit use SAND & SILT FLUSH at the rate of 3 gallons per 1000 gallons of flushing water. (When filling tank add water first then SAND & SILT FLUSH).

When using bucketing equipment SAND & SILT FLUSH should be added at the ratio of 1 gallon per 100 feet of 12 inch diameter sewer line or 2 to 3 gallons per 1000 gallons of flushing water.

EXTREME BLOCKAGE SITUATIONS

Sewer line should be cleaned at intervals of 350 feet by blocking the sewer line with sand bags. Proceed to the nearest manhole above the blockage and add SAND & SILT FLUSH at the rate of 3 to 5 gallons. Agitate thoroughly with sewer rod. Remove sand bags and flush system for 5 to 10 minutes.

Made in USA 

RM0415