

## DESIGNED FOR

**Wet Areas**      **Inclines**  
**Doorways**      **Walkways**  
**Locker Rooms**      **Kitchens**  
**Showers**      **Laundry Areas**  
**Steps**      **Water Plants**

## USE IN

**Schools**      **Sewer Treatment Plants**  
**Hospitals**      **Swimming Pools**  
**Nursing Homes**      **Commercial Buildings**  
**Motels**      **Municipal Buildings**  
**Industrial Plants**      **Packing Plants**

## FEATURES

**MARC Slip Guard** is especially designed as a safety product which is so necessary in complying with OSHA regulations.

**MARC Slip Guard** is a rubber-based paint that will resist the effects of water (it is water repellent) and chemical cleaners.

**MARC Slip Guard** dries quickly and bonds tightly to concrete, masonry and steel.

**MARC Slip Guard** is not affected by the action of alkali usually present in masonry surfaces, hence spotting and burning are eliminated. **MARC Slip Guard** penetrates the pores of masonry and forms a permanent bond with the surface.

VOC Content: Blue= 476 g/l, White = 477 g/l.

**MADE IN USA.**

**Net Contents: 5 Gallons**



# SLIP GUARD

## COLORS

**BLUE**       **WHITE**

**ESPECIALLY FORMULATED FOR  
PEOPLE CONCERNED ABOUT SAFETY**

**Ready-to-Use – Do Not Thin**

For Industrial and Institutional Use Only

<b>PIGMENT:</b> .....	<b>45.6%</b>	<b>VEHICLE:</b> .....	<b>54.4%</b>
<b>Titanium Dioxide</b> .....	<b>35%</b>	<b>Pliolite Resin</b>	
<b>Zinc Oxide</b> .....	<b>10%</b>	<b>and Plasticizers</b> .....	<b>24%</b>
<b>Silicates</b> .....	<b>55%</b>	<b>Solvent</b> .....	<b>76%</b>
	<b>100%</b>		<b>100%</b>



AN EXCLUSIVE FORMULA OF

**M-84**

MID-AMERICAN RESEARCH CHEMICAL CORP.  
P. O. BOX 927 · COLUMBUS, NE 68602-0927 · 800-228-8508

## RECOMMENDED USAGE

Surface must be dry and clean. Remove all loose or flaking paint or other loose particles with a wire brush. Apply **MARC Slip Guard** as it comes from the container. Do not thin. Apply with a brush or roller. Surface conditions should determine the method of application. One gallon covers from 100 to 300 square feet per coat, depending upon the type and porosity of the surface.

**NOTE:** Not suitable for use on asphalt shingles or on wood, aluminum or fiber-glass surfaces.

**MARC Slip Guard** should be stirred or shaken vigorously before application. It should also be stirred during application. **MARC Slip Guard** should not be stored for long periods of time without shaking or stirring.

**DANGER:** Contains petroleum distillates. Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and hot surfaces – No Smoking. Keep container tightly closed. Ground container and receiving equipment. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash exposed areas thoroughly after handling. Wear protective gloves and eye protection. Use other protective equipment as required. **IF SWALLOWED:** Do NOT induce vomiting. Immediately call a Poison Center or physician. **IF ON SKIN (or hair):** Remove immediately all contaminated clothing and wash before reuse. Rinse skin with water, and then wash with soap and water. If skin irritation occurs: Get medical attention. In exposed or concerned: Get medical attention. In case of fire: Use foam, carbon dioxide or dry chemical to extinguish. Store locked up in a cool, well-ventilated place. Dispose of in accordance with local, state and federal regulations.

**KEEP OUT OF REACH OF CHILDREN!**

HMIS/NFPA Ratings: Health-1, Flammability-2, Reactivity-0.

R0102