

**LUBRICATES AND CLEANS
LOOSENS NUTS AND BOLTS
DISPLACES WATER
NEVER DRIES
NON-CONDUCTIVE
PREVENTS RUST AND CORROSION**

- Engines, carburetors, nuts
- Distributor caps, bolts, dies
- Locks, hinges, meters, tools
- Airplanes, ships, tractors
- Trucks, trains, factories
- Laundries, vending machines
- Refrigeration equipment, guns
- Pipe fittings, moving parts

- Provides friction reduction
- Inhibits corrosion
- Non-drying lubricating oil
- Displaces moisture
- Cleans and removes rust
- Removes grease, dirt, build-up
- Frees frozen nuts, bolts, bearings

This product has unlimited applications for routine maintenance operations or wherever problems exist due to oxidation caused by exposure to unfavorable conditions. It is designed to penetrate and lubricate to reduce friction, displace water and moisture, stop squeaks and remove rust, grease, grime and prevent rust and corrosion on or in equipment, appliances, engines and other surfaces.

DISPLACES WATER

FOR USE ON AUTOMOBILES TO START WET OR DROWNED-OUT ENGINES, OR TO STOP BUILD-UP ON BATTERY TERMINALS.

DIRECTIONS FOR USE:

Read Cautions and Directions for Use carefully before using.

- **SHAKE WELL BEFORE USE.**
- MAY BE HARMFUL TO SOME PLASTICS AND PAINTED SURFACES. PRE-TEST ON SMALL AREA.
- Spray PENETRATING OIL onto frozen part or joint and tap the joint to set up vibration.
- In stubborn cases, respray the frozen part or joint and allow to soak in.

WARNING:

Contains gas under pressure; May explode if heated. Causes skin irritation. Suspected of causing cancer. May cause respiratory irritation, drowsiness or dizziness. May cause an allergic skin reaction. Keep away from heat, sparks, open flames, or hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized Container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before reuse. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Dispose of contents and container in accordance with local, state, and national regulations.



**KEEP OUT OF REACH
OF CHILDREN**

CONTAINS (CAS NO.):
Perchloroethylene (127-18-4), Trans-dichloroethylene (156-60-5), Carbon Dioxide (124-38-9), Butoxyethanol (111-76-2).



FEDERAL
REGULATIONS
PROHIBIT CFC
PROPELLANTS
IN AEROSOLS

HEALTH	3
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	B

HEALTH HAZARD	1	3	0	NFPA
				FIRE HAZARD
				REACTIVITY SPECIAL



Made in U.S.A.

R01-21



**BREAK-A-WAY II
PENETRATING OIL**

**NEW IMPROVED
FORMULA**



**DE-MOISTURANT
PREVENTS RUST
and
CORROSION**

NON-FLAMMABLE

**WARNING:
CONTAINS GAS UNDER PRESSURE;
MAY EXPLODE IF HEATED.**

NET WT. 18 OZ (510 g)

SOLD BY

M-104

**MID-AMERICAN RESEARCH CHEMICAL CORP.
P.O. BOX 927 • COLUMBUS, NE 68602-0927
800-228-8508**