

TRIPLE ACTION PENETRANT

MARC T-A-P is a triple action penetrant: The unique rapid freezing spray creates micro-fissures in the metal to help loosen stubborn nuts and bolts. The advanced-formula lubricant penetrates into the tightest spots and finally any rust is broken up and dissolved. Even severely seized and badly rusted nuts, bolts and parts are easily released, and future maintenance is made easier.

MARC T-A-P is specially formulated for the toughest penetrating lubricant jobs such as manifold bolts, exhaust flanges, and all exposed outdoor equipment in industrial, municipal, marine and farm applications. This combination ultra low VOC formula contains no chlorinated solvents or ozone depleters. MARC T-A-P is non-conductive to 33,000 volts so it can be used around most live electrical equipment. The 360° spray valve allows for use in any position and for access to hard-to-reach areas, and the large pad actuator prevents freezing of fingertips.

DIRECTIONS:

NOTE: Sudden drop in temperature can result in "thermal shock" which may cause crazing of some plastics and paint. While appropriate for use on many plastic and painted surfaces, always test first in an inconspicuous area before general use. Accumulated vapors from this product may reach ignition conditions in confined spaces. Always use with adequate ventilation. Shake well before using. Insert extension tube provided. Spray liberally for 5-10 seconds on surface to be lubricated. Target the bolt, nut or part and limit the amount of contact to the surrounding area. Wait 30 seconds to allow temperature reduction and to facilitate penetration. Loosen or remove part. Repeat if necessary.

WARNING: Flammable Aerosol. Contains gas under pressure; may explode if heated.

Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.

Warning: This product contains a chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

CONTAINS (CAS#): 1,1-Difluoroethane (75-37-6), Polysiloxane (63148-62-9), Methyl Isobutyl Ketone (108-10-1), Tall Oil Fatty Acid (61790-12-3).

KEEP OUT OF REACH OF CHILDREN

For further information consult Safety Data Sheet

R12-17

HMIS RATING:	
HEALTH	1
FLAMMABILITY	3
REACTIVITY	1
PERSONAL	A




MADE IN THE
U.S.A.



T-A-P

Triple Action Penetrant

- Freezing Action Loosens Bolts
- Lubricant Penetrates Deeply
- Non-Conducting to 33,000 Volts
- No Chlorinated Solvents
- Dissolves Rust
- No Ozone Depleters
- Ultra Low VOC



WARNING:

FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

NET WT. 9 OZ. (255 Grams)

M-114

MID-AMERICAN RESEARCH CHEMICAL CORP.
P.O. BOX 927 • COLUMBUS, NE 68602-0927
800-228-8508