



TECHNICAL DATA SHEET

**Product Name: GRAPHITE LUBRICANT
HIGH TEMPERATURE DRY FILM LUBRICANT**

Product Number: MARC 127

Features: **MARC 127 Graphite Lubricant** is a high temperature and extreme pressure lubricant. The dry graphite anti-seize coating resists dust and abrasive particles because it dries to a tack-free film. It withstands water wash-out, oil, alkalies and most acids. **MARC 127 Graphite Lubricant** forms a strong bond to metals as well as glass, rubber and most plastics. It will not wipe off easily, and may be used at higher temperatures than molybdenum disulfide-based dry film lubricants. **MARC 127 Graphite Lubricant** stops rust on parts in storage by forming an impenetrable rust-proof barrier to protect against corrosion and extend metal life. It may also be used as a release agent. The micro-sized film assures machining tolerances.

Applications: **MARC 127 Graphite Lubricant** is excellent for use in industrial plants, foundries, machine shops, vehicle manufacturers, steel mills, chemical plants, shipyards, oil fields, marine and mining operations, etc. Apply **MARC 127 Graphite Lubricant** to pipe threads, conveyors, road equipment, motors, gaskets, vending machines, parking meters, chains, sprockets, pump assemblies, rollers, wheels, hoists, etc. Use **MARC 127 Graphite Lubricant** on dies, drills, jigs and drills in storage for positive protection against corrosion and rust.

Specifications:

Weight Per Gallon: 6.93 pounds

Specific Gravity: 0.83

Form: Black fluid

Odor: Mild solvent

Working Temperature Range: -100°F to +850°F

Pressure Resistance: 18,000 psi

Water Solubility: Miscible

Evaporation Rate: Fast

R0920

MID-AMERICAN RESEARCH CHEMICAL CORP.

P. O. Box 927 • Columbus, NE 68602-0927 • Phone (402) 564-7104 • Fax (402) 563-1290 • Email: marc1@marc1.com • www.marc1.com