

Graphite Lubricant is an ideal extreme pressure lubricant. It is also a high heat resistant lubricant. It takes the place of cosmoline, and will positively stop rust on parts in storage. Does not have to be de-greased; forms an impenetrable rust proof barrier.

Lubricant film on all smooth and porous metals assures machine tolerances, as film is micro-size. This product is not affected by temperature variations. Works within temperature ranges of -100°F to +850°F.

Use on dies, drills, jigs, and drills in storage for positive protection against corrosion and rust.

DIRECTIONS:

Shake container well before using. Clean surface thoroughly. Apply a thin, even film. For best results, apply at temperatures of 60°F or above.



DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. May cause respiratory irritation, drowsiness or dizziness. Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. Avoid breathing fumes, mist, vapor and spray. Use only outdoors or in a well-ventilated area. Call a poison center or doctor if you feel unwell. Dispose of contents and container in accordance with local, state, and national regulations.

FIRST AID: If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If inhaled: Remove person to fresh air and keep comfortable for breathing.

Contains (CAS#): Acetone (67-64-1), Propane/n-Butane (68476-86-8), Isopropyl Alcohol (67-63-0), Graphite (1317-42-5).

KEEP OUT OF REACH OF CHILDREN

For further information consult Safety Data Sheet

R09-20

HMS RATING:	
HEALTH	2
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	B



GRAPHITE LUBRICANT

A HIGH TEMPERATURE DRY FILM LUBRICANT

Adheres to Metal, Glass, Rubber & Most Plastics

Extends Metal Life

DANGER
EXTREMELY FLAMMABLE AEROSOL.
CONTAINS GAS UNDER PRESSURE;
MAY EXPLODE IF HEATED.

See Back Panel For Additional Information

NET WT. 12 OZ. (340 Grams)

M-127

MID-AMERICAN RESEARCH CHEMICAL CORP.
P.O. BOX 927 • COLUMBUS, NE 68602-0927
800-228-8508