



GRAPHITE LUBRICANT

A HIGH TEMPERATURE
DRY FILM LUBRICANT

DANGER
EXTREMELY FLAMMABLE.
CONTENTS UNDER PRESSURE.

See Back Panel for Additional Information.

NET WT. 12 OZ (340 grams)

M-127

MID-AMERICAN RESEARCH CHEMICAL CORP.

P.O. BOX 927 • COLUMBUS, NE 68602-0927

800-228-8508

Graphite Lubricant is an ideal extreme pressure lubricant. It is also a high heat resistant lubricant. It takes the place of cosmoline, and will positively stop rust on parts in storage. Does not have to be de-greased; forms an impenetrable rust proof barrier.

Lubricant film on all smooth and porous metals assures machining tolerances, as film is micro-size. This product is not affected by temperature variations. Works within temperature ranges of 800°F to minus 78°F.

Use on dies, drills, jigs and drills in storage for positive protection against corrosion and rust.

DIRECTIONS: Shake well before using. Hold can in upright position. For best results apply at temperatures of 60°F or above.



DANGER: Extremely flammable gas. Highly flammable liquid and vapour. Contains gas under pressure; may explode if heated. Gas may reduce oxygen in confined spaces. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Rapid evaporation of the liquid may cause frostbite. Vapors are heavier than air and can cause suffocation by reducing available oxygen. May cause cardiac arrhythmia.

Other Cautions: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Eliminate all ignition sources if safe to do so. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. In case of a leaking gas fire: do not extinguish, unless leak can be stopped safely.

FIRST AID: Do not breathe mist, vapours, spray. Wash exposed skin thoroughly after handling. Wear protective gloves, protective clothing, eye protection, and face protection.

STORAGE: Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight.

R1114