

Degreases Engines, Tools, Metals, Concrete, Brick, Stone, Ceramic Tile, and Quarry Tile

Degreases motors on automobiles, trucks, tractors, lawn mowers, boats, etc. Excellent for degreasing industrial machinery, lawn and turf equipment, municipal equipment, concrete floors and driveways, boat bilges, vertical surfaces, ceilings, and hard-to-reach areas. Removes tar, asphalt, and grease from all types of vehicles, equipment and masonry surfaces such as brick, stone, concrete, etc. It emulsifies tar, asphalt, bitumen and asphalt base plastic cements and mono-form roofing compounds used by roofers.

NOTE: Always test product in an inconspicuous area before using.

DIRECTIONS SHAKE WELL BEFORE USING

For Engines:

1. Spray area to be degreased thoroughly by pushing straight down on the valve button at the top of the can.
2. Let it set for 10 to 20 minutes.
3. Hose off with strong stream of water.
4. Idle engine for 15 minutes immediately after hose-off to assure complete drying.

For Industrial Machinery:

1. Spray area to be degreased thoroughly by pushing straight down on the valve button at the top of the can.
2. Let it set for 10 to 20 minutes.
3. Wash equipment thoroughly and rinse with potable water before returning it to processing area.

For Tar & Asphalt Removal:

1. Spray area to be degreased and let it set at least 10 minutes.
2. Agitate if necessary and hose off with water.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. May be fatal if swallowed and enters airways.

Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.



READ THE SAFETY DATA SHEET (SDS) BEFORE USING THIS PRODUCT

CONTAINS (CAS No.): Petroleum distillates, hydrotreated light (64742-47-8), Methyl Soyate (67784-80-9), 1, 8-p-Menthadiene (5989-27-5), Diethylene Glycol n-Butyl Ether (112-34-5), 1,1-Difluoroethane (75-37-6).

For Commercial/Municipal/Industrial Use Only

R0120

HMIS RATINGS

FEDERAL
REGULATIONS
PROHIBIT
CFC
PROPELLANTS
IN AEROSOLS

HEALTH	2
FLAMMABILITY	2
REACTIVITY	0
PERSONAL PROTECTION	B



Made in U.S.A.

MARCO



TACKLE III

Super Concentrated Degreaser and Tar Remover JELLED FORMULATION WILL NOT RUN

Spray It On – Hose It Off With Water

Emulsifiable Organic Citrus Degreaser for
Engines, Concrete Floors or Any Other Areas
Where Grease, Tar or Asphalt has Accumulated.



Contains d-Limonene.
Does Not Contain Acids, Alkalis,
Chlorinated or Fluorinated Solvents.

IMPROVED VOC-COMPLIANT FORMULA

DANGER:
EXTREMELY FLAMMABLE AEROSOL.
CONTAINS GAS UNDER PRESSURE;
MAY EXPLODE IF HEATED.

Net Wt. 17 oz (1 lb 1 oz) (482 g)

M-138

MID-AMERICAN RESEARCH CHEMICAL CORP.
P.O. BOX 927 • COLUMBUS, NE 68602-0927
800-228-8508

