



TECHNICAL DATA SHEET

Product Name: TOUGH TAC CLEAR LUBE

Product Number: MARC 147

DESCRIPTION

A high tack lubricating gel which provides superior lubrication from -30°F to +600°F. Penetrates as an oil to the lubrication point then forms into a tacky, grease-like gel. M-147 contains PTFE (Polytetrafluoroethylene) for added friction reduction. Resists water washout and weathering. Residual film prevents rust and corrosion. Safe on most plastics and paints.

FOR USE BY

MACHINE SHOPS
LIGHT AND HEAVY MANUFACTURING
HVAC, PLUMBING & OTHER CONTRACTORS
AUTOMOTIVE
ALL REPAIR OPERATIONS

FOR USE ON

CHAINS – GEARS – HINGES
SPROCKETS – CABLE – WIRE ROPE
SLIDES – VALVES – BUSHINGS
PISTONS – SHAFTS – RINGS – SEALS
SLEEVES & PINS

FEATURES

FAST SET UP – HIGH TACK
FORTIFIED WITH PTFE
RECOATS GEARS & SHAFTS
CLEAN – CONVENIENT
EASY-TO-USE

SPECIFICATIONS

Appearance and Odor.....	Hazy Tan Liquid/Solvent Odor
Flammability.....	Flammable Aerosol
Specific Gravity.....	0.79-0.81
Propellant.....	Carbon Dioxide
VOC Content.....	12.7%

R0523

MID-AMERICAN RESEARCH CHEMICAL CORP.

P. O. Box 927 • Columbus, NE 68602-0927 • Phone 402-564-7104 • Fax 402-563-1290 • Email: marc1@marc1.com • www.marc1.com