



TECHNICAL DATA SHEET

Product Name: PENETRATING HI-TACK CLEAR LUBE
Product Number: MARC 147

DESCRIPTION

A high tack lubricating gel which provides superior lubrication from -30°F to +500°F. Penetrates as an oil to lubrication point then forms into a tacky, grease-like gel. Contains Teflon® for added friction reduction. Provides superior stringing action. Resists water washout and weathering. Residual film prevents rust and corrosion. Safe on most plastics and paints.

Teflon® - A registered Trademark of E.I. DuPont de Nemours & Co., Inc.

FOR USE BY

MACHINE SHOPS
LIGHT AND HEAVY MANUFACTURING
HVAC, PLUMBING & OTHER CONTRACTORS
AUTOMOTIVE
ALL REPAIR OPERATIONS

FOR USE ON

CHAINS – GEARS – HINGES
SPROCKETS – CABLE – WIRE ROPE
SLIDES – VALVES – BUSHINGS
PISTONS – SHAFTS – RINGS – SEALS
SLEEVES & PINS

FEATURES

FAST SET UP – HIGH TACK
FORTIFIED WITH TEFLON®
RECOATS GEARS & SHAFTS
CLEAN – CONVENIENT
EASY TO USE

SPECIFICATIONS

Appearance and Odor.....	Clear Liquid / Solvent Odor
Flash Point of Concentrate.....	>10°
Flammability.....	Extremely-Flammable Spray
Specific Gravity.....	0.78
Propellant.....	Liquified Petroleum Gas
Spray Pattern.....	Narrow Stream Spray
NFPA Fire Rating.....	Level 3 Aerosol
Packaging.....	12 x 13oz. Net Wt. Cans per case (20oz. Cans)

MID-AMERICAN RESEARCH CHEMICAL CORP.

P.O. Box 927 * Columbus, Nebraska 68602-0927 * Fax (402)563-1290 * Phone (402) 564-7104