



TECHNICAL DATA SHEET

Product Name: PRO-FLEX – CLEAR

Product Number: MARC 158

Uses: Leak Sealer, Roof Patch, Undercoating, Sound Deadener

Areas of Use: Skylights, Flashings, Air Vents, Cracks, Gutters, Shingles

Features & Benefits:

- Does not lose flexibility
- Protects against UV light
- Resists temperature extremes
- Impervious to water
- Abrasion resistant

Properties:

Form: Aerosol
Flammability: Extremely Flammable
Flash Point: -2°F
Specific Gravity: 0.82
Weight per Gallon: 6.84 pounds
VOC Content (less exempt solvents): 66.3%
Storage Temperature: 40°F to 100°F
Application Temperature: 50°F to 90°F
Durability: Excellent
Abrasion Resistance: Excellent
Freeze/Thaw Stability: Excellent
Dry Time (at 72°F and 50% humidity) tack-free: 10 minutes
Dry Time (at 72°F and 50% humidity) to recoat: 10 minutes
Dry Film Thickness-recommended: 1.5 mils
Gloss (60°): Flat
Odor: Aromatic solvent
Net Contents per Can: 15 ounces (425 grams)

R0413

MID-AMERICAN RESEARCH CHEMICAL CORP.

P.O. Box 927 * Columbus, Nebraska 68602-0927 * Fax (402)563-1290 * Phone (402) 564-7104