



PRO-FLEX CLEAR

**LEAK SEALER
ROOF PATCH
UNDERCOATING
SOUND DEADENER**

**Stays Flexible — Water-Tight Film
Protects Against Corrosion
Effective Over a Wide
Temperature Range**

DANGER EXTREMELY FLAMMABLE LIQUID AND VAPOR.
VAPORS MAY CAUSE FLASH FIRE.
CONTENTS UNDER PRESSURE. VAPOR HARMFUL
See other cautions on back panel.

NET WEIGHT 15.0 OUNCES (425 g)

M-158

MID-AMERICAN RESEARCH CHEMICAL CORP.
2470 14th Ave • Columbus, NE 68601
(800) 228-8508

**EFFECTIVE ON METALS, WOOD, ROOFING MATERIALS, TIN,
CONCRETE, ETC.
STAYS PLIABLE IN WINTER COLD, WILL NOT SAG, MELT OR
DRIP IN THE SUMMER HEAT.
RESISTS CRACKING, PEELING, AND ABRASION.**

Provides a super-thick, clear, durable and flexible rubberized film. Seals and acoustically reduces unwanted sound and vibration. Protects metal parts against the harmful effects of water, salt, sand and road chemicals.

USED BY: Roofing Contractors, Maintenance Crews, Building Supers, Plumbers, Auto and Diesel Repair Shops, Garages, Taxi Companies, Construction Companies, Machine Shops, Equipment Manufacturers, Air Conditioning Maintenance, Truck Fleet Maintenance, and Public Transportation Maintenance Operations.

FOR USE ON: Overlapping Seams, Gravel Stops, Chimney and Skylight Flashing, Vents and Pipe Flashing, Mobile Home and Camper Roof Seams, A/C Drip Pans, Gutters, Below-Grade Foundations, Minor Leak Repair, Automobiles.

DIRECTIONS: Shake can vigorously. Clean surface of dirt and rust. Hold can 12 inches from surface. Spray a thin even coat building up desired thickness. Remove over-spray with a cloth dampened with kerosene. To prevent clogging of tip, turn can upside down and depress tip for 2 seconds. Wipe and clean.

CONTAINS: Acetone 67-64-1, Toluene 108-88-3, Propane 74-98-6, VM&P Naphtha 64742-89-8, Heptane 142-82-5, N-Butane 106-97-8, Mineral Spirits 64742-47-8, Naphtha 64742-48-9, Solvent Naphtha 64742-94-5. **OTHER INGREDIENTS:** "Contents Partially Unknown", Solid Rubberized Resin.

WARNING: This product contains a chemical known to the state of California to cause cancer, birth defects or other reproductive harm.
Clear Coating Products Do Not Exceed 1.50 MIR



DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.



Prevention: Pressurized container: do not pierce or burn, even after use. Use only with adequate ventilation. Do not breathe dust/vapors/spray mist. Avoid contact with eyes/skin/clothing. Wear protective gloves/clothing/eye protection. Keep away from heat/sparks/open flames/hot surfaces. Do not eat/drink/smoke when using this product. Do not spray on naked flame or other ignition sources.



Response: In case of fire, use extinguishing powder or water spray. Immediately contact a doctor or POISON CONTROL CENTER if you feel unwell. If medical attention is needed, have product label at hand. **IF IN EYES:** Rinse with water for several minutes. Remove contact lenses if present. If eye irritation persists seek medical attention. **IF SWALLOWED:** Rinse mouth with water. Do not induce vomiting. **IF INHALED:** Remove to fresh air and rest in a comfortable breathing position. **IF ON SKIN:** Wash thoroughly with water. Remove all contaminated clothing.



Storage: Store locked up. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F.

Disposal: Dispose of product in accordance with local/regional/national/international regulations.

Additional Precaution Statements: Vapors may ignite explosively and cause a flash fire. Prevent buildup of vapors by opening windows and doors to achieve cross ventilation. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately inhaling the contents may be harmful or fatal. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear a NIOSH approved respirator during and after application. Follow respirator manufacturer's directions for respirator use.

KEEP OUT OF REACH OF CHILDREN • Read Safety Data Sheet Before Use

For further information consult Safety Data Sheet

R 6/15