



## TECHNICAL DATA SHEET

**Product Name: SILICONE SPRAY DRY LUBRICANT**

**Product Number: MARC 161**

- **PURE SILICONE**
- **HEAT STABLE FROM -58°F TO +575°F**
- **CAN BE USED AS A CLEANER AND LUBRICANT**
- **PROTECTS AGAINST FRICTION, CORROSION AND WEAR**
- **NON-CHLORINATED**
- **NON-STAINING, ODORLESS, COLORLESS**
- **RAPID DRYING FILM**
- **SAFE ON PLASTICS AND MOST ANY SURFACE**
- **LEAVES A MOISTURE-REPELLENT SUPER DRY FILM**

### ***Uses:***

**PACKAGING PLANTS  
PRINTING PLANTS  
GARMENT AND TEXTILE PLANTS  
MOLDING OPERATIONS  
GENERAL MAINTENANCE  
CONVEYORS • OVENS • TABLES • KNIVES • HINGES • SEWING MACHINES  
SCISSORS • GUIDE RAILS • HEAT SEALING EQUIPMENT • LATCHES • GEARS  
RUBBER • VINYL • METAL • GLASS • FABRIC • LAMINATES**

Appearance and Odor: Clear Liquid, Solvent Odor

Flash Point of Concentrate: 0°F

Flammability: Extremely Flammable Spray

Specific Gravity: 0.71

Weight per Gallon: 5.93 pounds

Propellant: Liquid Petroleum Gas

Spray Pattern: Circular Spray

R0816

MID-AMERICAN RESEARCH CHEMICAL CORP.

P.O. Box 927 • Columbus, Nebraska 68602-0927 • Fax (402)563-1290 • Phone (402) 564-7104