



SILICONE SPRAY

Dry Lubricant

**SLIDE and GLIDE
INDUSTRIAL GRADE**



DANGER: EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER MAY BURST IF HEATED. MAY CAUSE DROWSINESS OR DIZZINESS. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION. CAREFULLY READ PRECAUTIONS ON REAR PANEL.

NET WT. 9.25 OZ. (262 grams)

M-161

SOLD BY:
MID-AMERICAN RESEARCH CHEMICAL CORP.
P.O. BOX 927 COLUMBUS, NE 68602-0927
800-228-8508

**Contains NO Chlorinated Solvents
(NO 1,1,1-Trichloroethane)
NO CFCs**

A pure silicone dry lubricant release agent which reduces friction and eliminates sticking and binding on metal, rubber, glass, fabric and laminant surfaces. Treated areas repel moisture and are protected against corrosion and wear. Formulated with an ultra high viscosity, odorless, colorless and non-staining silicone. Heat stable at temperatures from -58°F to +575°F. Dries in seconds.

USED BY:

Printing trade, garment and textile industry, packaging plants, molding operations, industrial and processing plants.

DIRECTIONS:

Shake well before using. Spray in a sweeping motion, onto clean, dry surface from a distance of 6 to 10 inches. Repeat application periodically.

PRECAUTIONARY STATEMENT:

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Wear eye protection/face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. **IF SWALLOWED:** Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. **IF ON SKIN:** Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents and container in accordance with all local, regional, national and international regulations.

CONTAINS: Acetone (CAS#67-64-1), Butane (CAS#106-97-8), n-Heptane (CAS#142-82-5), Isobutane (CAS#75-28-5), Propane (CAS#74-98-6), Silicone (CAS#63148-62-9).

R09-17

**Read Safety Data Sheet before using.
KEEP OUT OF REACH OF CHILDREN!**

VOC Content: 59%



MADE IN U.S.A.
WITH GLOBALLY
SOURCED MATERIALS.