



TECHNICAL DATA SHEET

Product Name: FOAMING CHAIN & CABLE LUBRICANT
Product Number: MARC 166

DESCRIPTION

Provides a thick foam that clings to vertical surfaces. As foam breaks, lubricant penetrates into wire rope and chain mechanisms. Deposits a Molybdenum disulfide-based grease, and provides surfaces with superior lubricating properties. Protects against high temperature and extreme pressure environments. Grease will not break down, fly off or wash away with water or steam. Retains lubricating properties under heavy shock load, acidic environments and salt spray. Prevents surface oxidation and corrosion. Super high tack formula provides active lubricant dispersion while equipment is in operation.

FOR USE BY

SHIPYARDS – MINING – RAILROADS
FACTORIES – CONSTRUCTION
STEEL MILLS – ROAD EQUIPMENT
MATERIAL HANDLING COMPANIES
CONTAINERIZED SHIPPING COMPANIES

FOR USE ON

CHAINS – BOOMS - HOISTS
SAWS – CONVEYORS
CABLES – TOW LINES
WIRE ROPE – CRANES
WINCHES – BEARINGS
ROLLERS – WIRE CABLE
OPEN GEARS – SPROCKETS
CHAIN SAWS – DRAIN LINES
POWER DRIVES

FEATURES

SUPER FOAMING, QUICK PENETRATING GREASE
FORTIFIED WITH MOLY TO RESIST TEMPERATURE, WEAR, FRICTION,
HUMIDITY, SALT SPRAY, CHEMICAL VAPORS & WATER DAMAGE
RUST PROTECTIVE LUBRICANT FILM
HIGH PRESSURE AND EXTREME TEMPERATURE RESISTANCE

SPECIFICATIONS

Appearance and Odor.....	Thick Black Liquid, Petroleum Odor
Flash Point of Concentrate.....	>222°
Flammability.....	Flammable Spray
Specific Gravity.....	0.865
Propellant.....	Liquid Petroleum Gas
Spray Pattern.....	Narrow Stream
NFPA Fire Rating.....	Level 1 Aerosol
Packaging.....	12 x 15oz. Net Wt. Cans per case (20oz. Cans)
Salt Spray Resistant.....	72 Hours
Humidity Cabinet Resistance.....	60 Days

MID-AMERICAN RESEARCH CHEMICAL CORP.

P.O. Box 927 * Columbus, Nebraska 68602-0927 * Fax (402)563-1290 * Phone (402) 564-7104