



An extreme range lubricant and anti-seize coating that withstands temperatures from -110°F to +1050°F. Resists pressures up to 100,000 psi. Inert to water, oil, alkalies and many acids. Dry film coating will not attract dirt or dust. Contains pure Molybdenum Disulfide particles which burnish themselves into metal surfaces and provide a bonded lubricating film. Provides lubrication even under salt spray conditions.

INDUSTRY USES:

Foundries, automotive plants, vehicle maintenance, sewing trades, paper and corrugated converting, chemical plants, textile plants, woodworking, marine, agricultural and military equipment, road equipment, oil drilling equipment, aircraft maintenance, steel mills, mining operations, etc.

DIRECTIONS:

Shake can vigorously before application. Surface must be free from all loose rust, oil, grease and old paint. Spray with a sweeping motion, holding can 8 to 10 inches away from surface. Apply a thin uniform coating. Allow to set approximately 3 to 5 minutes before applying second coat.

IMPORTANT: To prevent clogging: After each use, invert can and spray a few short bursts to clear valve.

PATROL Dry Moly Lubricant

DANGER: Extremely flammable aerosol. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wear protective gloves/protective clothing/eye protection/face protection. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 49°C/120°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

FIRST AID: IF EXPOSED OR CONCERNED: Get medical advice/attention. **IF ON SKIN:** Wash off with soap and water. Get medical attention if irritation develops and persists. **IF IN EYES:** Rinse with water. Get medical attention if irritation develops and persists. **IF INHALED:** If symptoms develop move victim to fresh air. Get medical attention if symptoms persist. **IF SWALLOWED:** Rinse mouth. Get medical attention if symptoms occur.

CONTAINS (CAS No.): Methylene Chloride (75-09-2), Butane (106-97-8), Propane (74-98-6), Toluene (108-88-3) and Propylene Oxide (75-56-9).

Distributed by:
MID-AMERICAN RESEARCH
CHEMICAL CORP.
P.O. Box 927
Columbus, NE 68602-0927
402-564-7104



CAUTION: Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal. **KEEP OUT OF REACH OF CHILDREN.**

WARNING: This product can expose you to chemicals including Methylene Chloride and Propylene Oxide, which are known to the State of California to cause cancer, and Toluene, Methanol and Ethylene Glycol, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

See Safety Data Sheet for complete safety information


24 HOUR MEDICAL EMERGENCY: 1-866-836-8855

HMIS® RATING:	
HEALTH	3*
FLAMMABILITY	2
PHYSICAL HAZARD	2
PERSONAL PROTECTION	X

*=Chronic

PATROL

Dry Moly Lubricant



Fast Dry / Oil Free
Withstands Heavy Pressure
and High Temperature

DANGER: EXTREMELY FLAMMABLE.
VAPOR HARMFUL.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 14 OZ / 396 g

M-167

**MID-AMERICAN RESEARCH
CHEMICAL CORP.**

P.O. BOX 927 • COLUMBUS, NE 68602-0927



MADE IN THE
U.S.A.



PLEASE RECYCLE
WHEN EMPTY

R04-18