

This product is a high-temperature copper-based anti-seize agent, which can also be used as a protective coating. It works up to 1,800°F. MARC Anti-Seize Copper prevents galling, seizing and galvanizing action. It is non-melting, non-gumming and non-hardening, with excellent adhesion, extreme pressure resistance and water repellency. MARC Anti-Seize Copper also functions as a protective coating in highly corrosive environments. Contains no Methylene Chloride.

MARC Anti-Seize Copper provides outstanding protection against rust and corrosion on any type of metal, and ensures easy disconnection for bolts, spark plugs, threaded fittings, gaskets and bushings. It also works in automotive applications such as engine head bolts, exhaust manifold studs, starter and alternator bolts, spring bolts, lug nuts and spark plugs.

DIRECTIONS:

1. SHAKE CAN VIGOROUSLY.
2. MAKE SURE SURFACE IS CLEANED OF ALL DIRT, GREASE AND GRIME.
3. SPRAY LIBERAL AMOUNT FROM DISTANCE OF 8-10 INCHES. WIPE OFF EXCESS.
4. INVERT CAN AFTER USE AND SPRAY SHORT BURSTS TO CLEAR VALVE.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear eye protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Avoid breathing mist, vapors or spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Store in a well-ventilated place. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.

PELIGRO: Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Provoca irritación ocular. Puede causar somnolencia o mareos. Puede ser mortal en caso de ingestión y penetración en las vías respiratorias. Mantener alejado del calor, chispas, llamas abiertas y superficies calientes. -No fumar. No rocíe sobre una llama abierta u otra fuente de ignición. Recipiente a presión: No perforar ni quemar, incluso después de su uso. Protéjase de la luz solar. No lo exponga a temperaturas superiores a 50°C / 122°F. Almacenar en un lugar bien ventilado. Lávese bien las manos después de manipular. Use protección para los ojos. Si entra en contacto con los ojos: Enjuague cuidadosamente con agua durante varios minutos. Quítese las lentes de contacto, si lleva y es fácil de hacer. Continúe enjuagando. Si la irritación ocular persiste: busque atención o consejo médico. Evite respirar neblina, vapores o aerosoles. Úselo solo al aire libre o en un área bien ventilada. En caso de inhalación: lleve a la persona al aire libre y manténgala cómoda para respirar. Llame a un centro de intoxicaciones o un médico si no se siente bien. Almacenar en un lugar bien ventilado. En caso de ingestión: Llame inmediatamente a un centro de toxicología o un médico. No induzca el vomito. Deseche el contenido y el recipiente de acuerdo con las regulaciones locales, estatales y nacionales.

 **WARNING:** Cancer, birth defects or other reproductive harm - www.P65Warnings.ca.gov.

ADVERTENCIA: Cancer, Defectos de nacimiento u otros daños reproductivos - www.P65Warnings.ca.gov.

CONTAINS (CAS#): Polybutene (9003-29-6), Butane (106-97-8), Acetone (67-64-1), Propane (74-98-6), Heptane (142-82-5).

KEEP OUT OF REACH OF CHILDREN

For further information consult Safety Data Sheet

HMIS RATING:	
HEALTH	1
FLAMMABILITY	3
REACTIVITY	1
PERSONAL	B



R03-22



HIGH TEMP ANTI-SEIZE COPPER

- Contains Copper-Moly Combo
- Protects Against Galling
- Protects Against Seizing
- Lubricates and Seals
- Waterproof
- Works from -60°F to 1,800°F
- Synthetic Oil-Based Formula

DANGER/PELIGRO

EXTREMELY FLAMMABLE AEROSOL.
CONTAINS GAS UNDER PRESSURE;
MAY EXPLODE IF HEATED.

AEROSOL EXTREMADAMENTE INFLAMABLE.
CONTIENE GAS A PRESIÓN;
PUEDE EXPLOTAR SI SE CALIENTA.

NET WT. 12 OZ. (340 Grams)

M-168

MID-AMERICAN RESEARCH CHEMICAL CORP.
P.O. BOX 927 • COLUMBUS, NE 68602-0927
800-228-8508