



HIGH TEMP ANTI-SEIZE COPPER

- Protects Against Galling
- Protects Against Seizing
- Lubricates and Seals
- Waterproof
- Works up to 2,000°F

DANGER: EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER MAY BURST IF HEATED. MAY CAUSE RESPIRATORY IRRITATION. HARMFUL IF SWALLOWED. MAY BE HARMFUL IN CONTACT WITH SKIN. MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION. SUSPECTED OF CAUSING CANCER. VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

Read rear panel for additional precautions.

NET WT 14 OZ (396 g)

M-168

SOLD BY:

MID-AMERICAN RESEARCH CHEMICAL CORP.
P.O. BOX 927 COLUMBUS, NE 68602-0927
800-228-8508

This product is a high-temperature copper-based anti-seize agent, which can also be used as a protective coating. It works up to 2,000°F. MARC Anti-Seize Copper prevents galling, seizing and galvanizing action. It is non-melting, non-gumming and non-hardening, with excellent adhesion, extreme pressure resistance and water repellency. MARC Anti-Seize Copper also functions as a protective coating in highly corrosive environments.

MARC Anti-Seize Copper provides outstanding protection against rust and corrosion on any type of metal, and ensures easy disconnection for bolts, spark plugs, threaded fittings, gaskets and bushings. It also works in automotive applications such as engine head bolts, exhaust manifold studs, starter and alternator bolts, spring bolts, lug nuts and spark plugs.

DIRECTIONS:

SPRAY PRODUCT ONLY AT TEMPERATURES ABOVE 60°F

1. Shake can vigorously for one minute after mixing ball begins to rattle.
2. Make sure surface is cleaned of all dirt, grease and grime.
3. Spray liberal amount from distance of 8-10 inches.
4. Invert can after use and spray short bursts to clear valve.

Contains [CAS#]: Methylene Chloride [75-09-2], Copper [7440-50-8], Butane [106-97-8], Propane [74-98-6], Isobutane [75-28-5].

PRECAUTIONARY STATEMENT:

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Do not handle until all safety precautions have been read and understood. Collect spillage. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. If skin irritation occurs: Get medical advice/attention. In case of fire: Use water fog, dry chemical or carbon dioxide to extinguish. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Keep cool. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents and container in accordance with all local, regional, national and international regulations.

**NOT FOR RETAIL SALE.
FOR INDUSTRIAL / COMMERCIAL USE ONLY.
NOT FOR SALE IN THE STATE OF CALIFORNIA.**



R12-19



MADE IN THE U.S.A.
with globally sourced
materials