



TECHNICAL DATA SHEET

Product Name: STRIPING PAINT – HANDICAP BLUE

Product Number: MARC 170

Features: This formulation is especially for handicap line striping. It features quick and easy application to concrete, blacktop, soil, grass, gravel and most other surfaces. It has good hide with one application. Because of its universal spray head, MARC Striping Paint is compatible with almost all four-wheeled striping machines. Use with the MARC Stripe Marking Machine.

Suggested Uses:

Streets – Crosswalks – Parking Stalls – Football Fields – Warehouses
Baseball Fields – Track Marking – Playgrounds

Properties:

Flammability: Flammable
Flash Point: -4°F
Specific Gravity: 0.83
Weight per Gallon: 6.93
Solids Content: approx. 31%
VOC Content: approx. 49%
MIR Value: 0.64
HAPs Content: 3%
Storage Temperature: 40°F to 100°F
Application Temperature: 50°F to 90°F
Durability: Excellent
Abrasion Resistance: Excellent
Freeze/Thaw Stability: Excellent
Stripe Width: 2" to 4" wide
One Can will Stripe: 250 linear feet
Dry Time (at 72°F and 50% humidity) to Touch: 15 minutes
Dry Time (at 72°F and 50% humidity) to Traffic: 60 minutes
Dry Film Thickness: 1.5 mil
Gloss (60°): Flat
Net Contents per Can: 18 ounces (511 grams)
Shipping Classification: Paint, Limited Quantity

R0817

MID-AMERICAN RESEARCH CHEMICAL CORP.

P.O. Box 927 • Columbus, Nebraska 68602-0927 • Fax (402)563-1290 • Phone (402) 564-7104 • www.marc1.com