



TECHNICAL DATA SHEET

Product Name: PRO-FLEX RUBBERIZED COATING

Product Number: MARC 178

SPECIFICATIONS:

Uses: Leak Sealer, Roof Patch, Undercoating, Sound Deadener

Form: Aerosol

Color: Black

Odor: Solvent

Density: 0.8767 g/cm³

Weight per Gallon: 7.32 pounds

Flash point: -156 °F (-104.4 °C) (of propellant)

Boiling point: 298.4 °F (147.8 °C)

pH: Not Applicable

Physical State: Liquid.

Vapor Pressure: 53 - 63 psig @ 70°F

Solubility in Water: None

Viscosity: High

Flexibility: Excellent

Temperature Range: Excellent

Durability: Excellent

Water/Salt/Sand/Chemical Resistance: Excellent

Sag/Melt/Drip Resistance: Excellent

Heat Resistance: Excellent

Cracking/Peeling/Abrasion Resistance: Excellent

Paintable: Yes

Dry Times: 12 hours to touch, 24 hours to cure
(depending upon thickness)

Rev. 0612

MID-AMERICAN RESEARCH CHEMICAL CORP.

P.O. Box 927 * Columbus, Nebraska 68602-0927 * Fax (402)563-1290 * Phone (402) 564-7104