

• WORKS INSTANTLY •

STOPS CORROSION • PAINTABLE •

Restores Any Iron or Steel Surface

Use On Railings, Furniture, Tools, Cars, Truck, Trailers, Etc.

## DANGER:

Extremely Flammable Liquid and Vapor.

Vapors May Cause Flash Fire. Contents Under Pressure.

Vapor Harmful. See other cautions on back panel.

Net Weight: 12 oz. (340 g)

M-179

MID-AMERICAN RESEARCH CHEMICAL CORP. P. O. BOX 927 • COLUMBUS, NE 68602-0927 800-228-8508

## DIRECTIONS

- 1. For best results, use when can is between 50°F and 90°F (10°C and 32°C)
- 2. Shake can at least one minute after rattle is heard and occasionally during use.
- Use a wire brush or sandpaper to remove as much loose and flaky rust as possible.
- 4. Spray surface with steady even strokes at a distance of 8 to 12 inches. A chemical reaction will cause the rust to turn black. Allow 24 hours before applying a second coat or when topcoating with a different coating.
- 5. If clogging develops, turn sprayhead ¼ turn or remove and clean sprayhead slot. DO NOT stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.
- 6. To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose partially empty cans responsibly. DO NOT incinerate or compact.

Contains: Acetone 67-64-1, Propane 74-98-6, Talc 14807-96-6, Isobutyl Acetate 110-19-0, N-Butane 106-97-8, Propylene Glycol Industrial 57-55-6, Methyl Isobutyl Ketone 108-10-1, Methyl Propyl Ketone 107-87-9, Glycol Ether EP 2807-30-9, Xylene 1330-20-7, PM Acetate 108-65-6. OTHER INGREDIENTS: "Contents Partially Unknown", Soya Alkyd Resin.

WARNING: This product contains a chemical known to the State of California to cause cancer.

Rust Converter Products Do Not Exceed 1.00 MIR




DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Prevention: Pressurized container: do not pierce or burn, even after use. Use only with adequate ventilation. Do not breathe dust/vapors/spray mist. Avoid contact with eyes/skin/dothing. Wear protective gloves/clothing/eye protection. Keep away from heat/sparks/open flames/hot surfaces. Do not eat/drink/smoke when using this product. Do not spray on naked flame or other ignition sources.

Response: In case of fire, use extinguishing powder or water spray. Immediately contact a doctor or POISON CONTROL CENTER if you feel unwell. If medical attention is needed, have product label at hand. IF IN EYES: Rinse with water for several minutes. Remove contact lenses if present. If eye irritation persists seek medical attention. IF SWALLOWED: Rinse mouth with water. Do not induce vomitting. IF INHALED: Remove to fresh air and rest in a comfortable breathing position. IF ON SKIN: Wash thoroughly with water. Remove all contaminated clothing.

Storage: Store locked up. Protect from sunlight and do not expose to temperatures

exceeding 50°C/122°F.

Disposal: Dispose of product in accordance with local/regional/national/international



Additional Precaution Statements: Vapors may ignite explosively and cause a flash fire. Prevent buildup of vapors by opening windows and doors to achieve cross ventilation. Reports have associated repeated and prolonged occupational overexposure

to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately inhaling the contents may be harmful or fatal. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear a NIOSH approved respirator during and after application. Follow respirator manufacturer's directions for respirator use.

KEEP OUT OF REACH OF CHILDREN Read Safety Data Sheet Before Use







