



ULTRA HI-IMPACT GREASE

FOR

Heavy Equipment
Oil Fields
Farms
Sewage Plants
Mills
Elevators

Industry
City and County
Cement Plants
Construction
Food Plants
Automotive

CAUTION:

KEEP OUT OF REACH OF CHILDREN.
Do not take internally. See side panel for
additional precautionary information.

NET WT. 14 OZ.(397 grams)

M-189

SOLD BY
MID-AMERICAN RESEARCH CHEMICAL CORP.
P.O. BOX 927 COLUMBUS, NE 68602

ULTRA HI-IMPACT GREASE

FEATURES

Will Not Pound Out
Withstands High Temperatures
Reduces Down Time
Extremely Heat Resistant
Contains Rust and Corrosion Inhibitors
Extends Equipment Life

DESCRIPTION

Special formulated additives allow this multi-purpose ULTRA HI-IMPACT GREASE to stand up to extreme impact and pounding pressure in heavy equipment. Whether equipment is new or old, to extend the life and reduce repairs and down time, ULTRA HI-IMPACT GREASE with its ability to not spatter or pound out should be used. Special additives in our ULTRA HI-IMPACT GREASE allow it to perform under extreme heavy impact and pounding pressures common in heavy equipment. Our special formulation allows our ULTRA HI-IMPACT GREASE to perform at temperatures as high as 550°F and will provide that extra long life at a load of 65 TIMKEN. Its special formulation with rust, corrosion and oxidation inhibitors resists acids, dirt, water, and high heat problems.
NLGI 2-21/2

**PUMP IN ULTRA HI-IMPACT GREASE UNTIL
ALL OLD GREASE COMES OUT.**

CAUTION:

KEEP OUT OF REACH OF CHILDREN. Do not take internally. Do not ingest. If this should occur, drink large volumes of water and seek medical attention. Avoid storage of product in freezing temperatures. Discard according to federal, state and local regulations. KEEP OUT OF REACH OF CHILDREN.