



THERMO- GUARD GREASE (NON-MELTING) FOR

Heavy Equipment
Oil Fields
Farms
Sewage Plants
Mills
Elevators

Industry
City and County
Cement Plants
Construction
Food Plants
Automotive

**PUMP IN THERMO-GUARD GREASE UNTIL
ALL OLD GREASE COMES OUT.**

CAUTION:

Do not ingest. If this should occur, drink large volumes of water and seek medical attention. Avoid storage of product in freezing temperatures. Keep container sealed when not in use. Rinse empty container before discarding in an authorized landfill site. **KEEP OUT OF REACH OF CHILDREN.**

NET WT. 14 OZ. (397 GRAMS)

M-190

**SOLD BY
MID-AMERICAN RESEARCH CHEMICAL CORP.
P.O. BOX 927 COLUMBUS, NE 68602**

THERMO-GUARD GREASE (NON-MELTING)

FEATURES

Extremely Heat Resistant
Reduces Shock and Noise
Does Not Thin Out
Extends Equipment Life
Contains Rust and Corrosion Inhibitors
Reduces Down Time

THERMO-GUARD is a specially formulated ALL PURPOSE grease that withstands high heat generated by equipment that will normally break down other greases. With its special thermal additives, it is effective under extreme pressure, and will provide superior adhesive and cohesive properties for heavy-duty service. It is specially formulated to resist weather temperature extremes, water, acids, dirt, steam and oxidation, and will be effective at a 65 TIMKEN load under heavy shock and impact pressures. THERMO-GUARD will withstand heat to 550°F.

NLGI 2

R09-94