

FEATURES

MARC Tartan Floor Sealer/Finish is the ideal product to both seal and top-coat rubber or other synthetic gym floors. Because these types of floors are highly resilient, regular floor finishes may wear prematurely. **MARC Tartan Floor Sealer/Finish** is specifically designed to give a long-lasting, beautiful appearance. Its metal crosslinked formulation results in high durability with easy removal.

WARNING: Contains glycol ether. Causes serious eye irritation. Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves and eye protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If on skin: Wash off thoroughly with water. Do not take internally. Use with adequate ventilation. Keep container closed when not in use. **KEEP OUT OF REACH OF CHILDREN! KEEP FROM FREEZING.**

HMIS/NFPA Ratings: Health-0
Flammability-0, Reactivity-0.



MADE IN USA.

Net Contents: 5 Gallons



TARTAN FLOOR SEALER/FINISH

**Especially designed for rubber
or synthetic gym floors.**

NEW IMPROVED FORMULA

- **EXCELLENT GLOSS**
- **EXCEPTIONAL WEAR**
- **BALANCED PERFORMANCE**
- **EXTREMELY DURABLE**
- **OUTSTANDING LEVELING**

**Coverage:
2,000 to 2,500 Square Feet per Gallon**

An Exclusive Formula of

M-224

**MID-AMERICAN RESEARCH CHEMICAL CORP.
P. O. BOX 927 · COLUMBUS, NE 68602-0927 · 800-228-8508**

**Detergent Resistant
Self-Leveling
Will Not Yellow
Scuff and Mark Resistant
Non-Streaking
Slip Retardant**

DIRECTIONS

Mop or strip floor as needed. Floor should be thoroughly clean and dry. Apply **MARC Tartan Floor Sealer/Finish** in even coats up to 2,500 square feet per gallon using a clean mop or lamb's wool applicator. Apply two to three coats for maximum gloss and durability.

Allow 30 to 60 minutes between the first and second coats during low humidity, and longer times between subsequent coats. When humidity is high (70% or above), allow as long as several hours before recoating.

To maintain appearance, floor may occasionally be buffed. Clean floor thoroughly before buffing with a neutral floor cleaner like MARC 239 Renew.

STRIPPING

Can be effectively removed with MARC 39 Plus or MARC 272 Once Over.

RM1219