

DISSOLVES:

**GREASE
FAT
SLIME**

DIRECTIONS

Designed especially to dissolve grease and slime in lift stations, sewage treatment plants, cesspools, grease traps, drainage fields, and sludge aeration beds.


LIFT STATIONS: To be poured directly into manhole or lift station pit. If there is a heavy accumulation on side walls of manhole or lift station pit, **Pine Clean Lift Station Maintainer PT** should be poured or sprayed through a MARC Pressure Sprayer (Hudson type) directly on side walls. **Pine Clean Lift Station Maintainer PT** is a pine - based product and will float on top of water. For best results it should be used in sufficient quantities to assure a 1 to 3 inch cap on the surface.

FORMULA TO DETERMINE AMOUNT OF
TO BE ADDED TO LIFT STATION:

ROUND LIFT STATION: Diameter in FEET x Diameter in FEET ÷ 2 x Depth of Cap in INCHES = Gallons of **Pine Clean Lift Station Maintainer PT** required.

RECTANGULAR OR SQUARE LIFT STATION: Length in FEET x Width in FEET x Depth of Cap in INCHES x .6 = Gallons of **Pine Clean Lift Station Maintainer PT** required.

SEPTIC TANKS - CESSPOOLS: Add 1 pint per 500 gallon capacity for initial treatment. Use 1 to 2 oz. per week for each 500 gallon capacity as preventive maintenance treatment.

DRAINS: Pour one-half cup (4 oz.) of concentrate into drains. Allow to remain overnight, if possible -- at least two to four hours. **DO NOT ALLOW LIQUID OR VAPORS OF LIQUID TO COME IN CONTACT WITH FOOD.** **Made in USA** 

HMIS/NFPA Ratings: Health-2, Flammability-2, Reactivity-0.

Net Contents: 5 Gallons

MARC 



LIFT STATION MAINTAINER



NATURAL PINE SOLVENT BASE

- ★ IMPROVES LIFT STATION EFFICIENCIES
- ★ ELIMINATES DOWN TIME
- ★ CONTROLS OBJECTIONABLE ODORS
- ★ EASY SOLUTION FOR DIRTY JOBS



An Exclusive Formula Of

M-228-PT

MID-AMERICAN RESEARCH CHEMICAL CORP.
P. O. BOX 927 · COLUMBUS, NE 68602-0927 · 800-228-8508

**TIME SAVER
MONEY SAVER
WORK SAVER
READY-TO-USE
BIODEGRADABLE
ECONOMICAL**

FEATURES

Dissolves fats and greases in catch basins, drain lines, etc.

Quickly dissolves grease and slime in septic tanks, cesspools, grease traps, drainage fields, and ditches. Controls bacterial odors with no harmful side effects to beneficial digestive organisms.

DANGER: Contains petroleum distillates and dipentene. Flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. Causes eye irritation. May be fatal if swallowed and enters airways. Harmful if inhaled. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure. Do not take internally. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Keep container tightly closed. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only in a well-ventilated area. Wear protective gloves and eye protection. If on skin or hair: Immediately take off all contaminated clothing. Rinse skin and hair with water. Wash contaminated clothing before reuse. If swallowed: Immediately call a physician. Do NOT induce vomiting. In inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical attention. Call a poison center or doctor if you feel unwell. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. In case of fire: Use water fog, foam dry chemical or carbon dioxide to extinguish. Store locked up in a cool, well-ventilated area. Dispose of in accordance with federal, state and local regulations. **Keep Out of Reach of Children!** RM0715