

FEATURES

MARC Polyurethane Wood Seal is specifically designed as a sealer undercoat for MARC Polyurethane Gym Finish.

MARC Polyurethane Wood Seal dries to a clear transparent film that will not discolor the floor. Floors sealed with **MARC Polyurethane Wood Seal** require less coats of finish.

DANGER: Contains petroleum distillates and xylene. Flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. Causes eye irritation. May be fatal if swallowed and enters airways. Harmful if inhaled. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure. Do not take internally. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Keep container tightly closed. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only in a well-ventilated area. Wear protective gloves and eye protection. If on skin or hair: Immediately take off all contaminated clothing. Rinse skin and hair with water. Wash contaminated clothing before reuse. If swallowed: Immediately call a physician. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical attention. Call a poison center or doctor if you feel unwell. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. In case of fire: Use water fog, foam dry chemical or carbon dioxide to extinguish. Store locked up in a cool, well-ventilated area. Dispose of in accordance with federal, state and local regulations.

Keep Out of Reach of Children!



HMIS/NFPA Ratings: Health-2, Flammability-2, Reactivity-0.

MADE IN USA.



POLYURETHANE WOOD SEAL

- **EXTREMELY HARD**
- **EXCELLENT PENETRATION**
- **ENHANCES APPEARANCE**
- **EXCELLENT BASE FOR POLYURETHANE GYM FINISH**

Coverage: 350 to 500 Square Feet per Gallon

Drying Time: 10 to 24 Hours (depending upon humidity)

VOC Content: 615 g/1

For industrial and institutional use only.

An Exclusive Formula of **M-258**

MID-AMERICAN RESEARCH CHEMICAL CORP.
P. O. BOX 927 · COLUMBUS, NE 68602-0927 · 800-228-8508

**READY TO USE
NO MIXING – DO NOT THIN
EXCELLENT COVERAGE**

RECOMMENDED USES

MARC Polyurethane Wood Seal is recommended as a sealer for gymnasiums, desks, woodwork, church pews and any other interior wooden surfaces.

HOW TO USE

When using on bare wood, apply two coats of **MARC Polyurethane Wood Seal** using a lamb's wool applicator. Abrade floor between coats with MARC 826 Gym Floor Conditioning Pads. Allow adequate drying time between coats.

When the seal is thoroughly dry, apply the paint markings. When the paint is thoroughly dry, scuff up the paint to promote adhesion to the gym finish.

It is always best to apply MARC Polyurethane Gym Finish sometime within 24 to 72 hours, so the finish coat will bite into the sealer coat, thereby fusing all coats together rather than having skin coats, one on top of the other.

Application equipment may be cleaned with MARC 234 Woody II.

NET CONTENTS: 5 Gallons

R0120