

FEATURES

MARC Hi-Solids Polyurethane Gym Finish is a modern polyurethane finish. This finish is so light in color that it reduces yellowing and darkening even after many coatings. This feature alone saves thousands of dollars in maintenance by reducing heavy sandscreening and re-sanding of floors every few years. **MARC Hi-Solids Polyurethane Gym Finish** is tough, extremely hard and durable, and withstands any community activity. It provides extremely high luster, excellent gloss retention, outstanding rubber burn resistance, good adhesion and is in a class by itself for abrasion resistance. There is never any deviation and complete uniformity is assured.

DANGER: Contains petroleum distillates and xylene. Flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. Causes eye irritation. May be fatal if swallowed and enters airways. Harmful if inhaled. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure. Do not take internally. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Keep container tightly closed. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe the mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only in a well-ventilated area. Wear protective gloves and eye protection. If on skin or hair: Immediately take off all contaminated clothing. Rinse skin and hair with water. Wash contaminated clothing before reuse. If swallowed: Immediately call a physician. Do NOT induce vomiting. In inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical attention. Call a poison center or doctor if you feel unwell. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. In case of fire: Use water fog, foam dry chemical or carbon dioxide to extinguish. Store locked up in a cool, well-ventilated area. Dispose of in accordance with federal, state and local regulations.

Keep Out of Reach of Children!



HI-SOLIDS POLYURETHANE GYM FINISH

51% SOLIDS

- **EXTREMELY HARD**
- **EXCELLENT DURABILITY**
- **HIGH LUSTER**
- **MARK RESISTANT**
- **EXCELLENT GLOSS RETENTION**

VOC Content: 450 g/l
(VOC Compliant in Many Areas)

Coverage: 600 to 800 Square Feet per Gallon

Drying Time: 36 to 72 Hours
(depending upon humidity)

An Exclusive Formula Of M-269

MID-AMERICAN RESEARCH CHEMICAL CORP.
P. O. BOX 927 · COLUMBUS, NE 68602-0927 · 800-228-8508

- **READY-TO-USE**
- **NO MIXING**
- **EXCELLENT COVERAGE**

RECOMMENDED USES

MARC Hi-Solids Polyurethane Gym Finish is recommended for use as an interior finish on wood gymnasium floors, wood dance floors and wood aerobic floors where a tough, durable, highly lustrous finish is desired. A base coat of **MARC Polyurethane Wood Seal** assures a consistent bond of this product.

DIRECTIONS FOR USE

Apply all necessary markings and let the paint dry 24 hours before applying **MARC Hi-Solids Polyurethane Gym Finish**.

Do not thin product. Apply a coat of **MARC Hi-Solids Polyurethane Gym Finish** with an E-Z Way Applicator, making a 24" pass from one end of the floor to the other end, covering the entire floor. If using a 16" lamb's wool applicator, use even strokes, working an area about six feet wide the full length of the floor. Be sure to wipe out all air bubbles. It is important to ventilate the gym after the finish has set for six hours, especially if the humidity level is over 70%.

It is always best to apply the second coat of **MARC Hi-Solids Polyurethane Gym Finish** sometime between 24 and 72 hours, so that the second coat will bite into the first coat, thereby fusing all coats together. Keep regular traffic off the floor for 7 to 10 days to allow finish to cure thoroughly. Clean application equipment with **MARC Woody II**.

HMIS/NFPA Ratings: Health-2, Flammability-2, Reactivity-0.

Manufactured in the USA from globally sourced materials.

Net Contents: 5 Gallons

R0121