



# TECHNICAL DATA SHEET

**Product Name: Black Super Strip Pad**

**Product Number: MARC 825**

**Description:** The **MARC 825 Black Super Strip Pad** is constructed of polyester fibers in an open texture nonwoven fabrication. Abrasive particles are distributed throughout the pad and adhered to the nonwoven construction with a sturdy adhesive.

**Properties:**

Property	Value
Thickness	0.63 inch 16 mm
Weight	47 osy (ounces per square yard) 1,594 gsm (grams per square meter)
Fiber Type	Recycled Polyester
Binder System	Cross-linkable Water-based
Binder Application	Spray/Dip
Abrasive Application	Spray/Dip
Abrasive	Yes
Color	Black
Pack	5 per case



**Use:** This is a very aggressive stripping pad for use with water based floor stripping solution to remove worn and soiled floor finishes or sealers. It is for use on standard electric floor machines or automatic scrubbers, and ideal for use on machines with speeds up to 350 rpm.

**Construction:** The **MARC 825 Black Super Strip Pad** is constructed of polyester fibers along with synthetic adhesives that will not be notably affected by water or cleaners used in standard floor maintenance. The abrasives used in this product are synthetic. This pad has been designed for use on both sides. Polyester fiber used in our pads comes from 100% post-consumer and industrial recycled waste product. They are formulated to biodegrade in a fraction of the time that it takes conventional floor pads once discarded into an active landfill. Water-based latex resins are used in the manufacturing process. No phenol-formaldehyde resins are used in the binding process. Shipping cartons contain at least 45% recycled material.

**Directions for Use:** Dust mop or sweep floors prior to stripping. Use pad until soil and finish are removed from floor. Pick up stripping or cleaning solution with a mop, wet vacuum or automatic scrubber. Rinse floor and let dry prior to recoating or opening to traffic.

R017

MID-AMERICAN RESEARCH CHEMICAL CORP.

P. O. BOX 927 • COLUMBUS, NE 68602-0927 • 402-564-7104 • FAX 402-563-1290 • www.marc1.com