



INVERTED PRECAUTION BLUE SPRAY PAINT

Environmentally Formulated
Water-Base

V.O.C. COMPLIANT

NET WEIGHT 13.0 OUNCES (369 g)

DANGER EXTREMELY FLAMMABLE LIQUID AND VAPOR.
VAPORS MAY CAUSE FLASH FIRE.
CONTENTS UNDER PRESSURE. VAPOR HARMFUL

See other cautions on back panel.

M-847

MID-AMERICAN RESEARCH CHEMICAL CORP.
2470 14th Ave • Columbus, NE 68601
(800) 228-8508

NON-CLOGGING EXCELLENT COVERAGE ON SOIL, GRASS, GRAVEL AND PAVEMENT

A heavy-duty, industrial paint with a water base formula that is fast drying, durable and non-clogging. Use in marking construction, excavation sites, underground utilities, landscaping, etc. Will not wash away or damage grass.

DIRECTIONS

1. For best results, use when can temperature is between 40°F and 90°F.
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Invert can and hold 4 to 6 inches above surface to be marked. Press sprayhead to the side to actuate.
4. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. DO NOT stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.
5. To clear sprayhead for future use, turn can right side up and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

Contains: VM&P Naphtha 64742-89-8, Propane 74-98-6, Calcium Carbonate 1317-65-3, N-Butane 106-97-8, Mineral Spirits 64742-47-8, Titanium Dioxide 13463-67-7. OTHER INGREDIENTS: "Contents Partially Unknown", Water 7732-18-5.

WARNING: This product contains a chemical known to the state of California to cause cancer. Ground Marking Coatings Do Not Exceed 1.20 MIR



DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. Suspected of causing cancer.



Prevention: Pressurized container: do not pierce or burn, even after use. Use only with adequate ventilation. Do not breathe dust/vapors/spray mist. Avoid contact with eyes/skin/clothing. Wear protective gloves/clothing/eye protection. Keep away from heat/sparks/open flames/hot surfaces. Do not eat/drink/smoke when using this product. Do not spray on naked flame or other ignition sources.



Response: In case of fire, use extinguishing powder or water spray. Immediately contact a doctor or POISON CONTROL CENTER if you feel unwell. If medical attention is needed, have product label at hand. IF IN EYES: Rinse with water for several minutes. Remove contact lenses if present. If eye irritation persists seek medical attention. IF SWALLOWED: Rinse mouth with water. Do not induce vomiting. IF INHALED: Remove to fresh air and rest in a comfortable breathing position. IF ON SKIN: Wash thoroughly with water. Remove all contaminated clothing.



Storage: Store locked up. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F.

Disposal: Dispose of product in accordance with local/regional/national/international regulations.

Additional Precaution Statements: Vapors may ignite explosively and cause a flash fire. Prevent buildup of vapors by opening windows and doors to achieve cross ventilation. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately inhaling the contents may be harmful or fatal. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear a NIOSH approved respirator during and after application. Follow respirator manufacturer's directions for respirator use.

KEEP OUT OF REACH OF CHILDREN • Read Safety Data Sheet Before Use