



TECHNICAL DATA SHEET

Product Name: **INVERTED FLUORESCENT GREEN SPRAY PAINT**

Product No: **MARC 848**

Container: 16 Fluid Ounce Aerosol Can

Label Weight: 16 Fluid oz. can – 13.0 oz. (369 GM)

Propellant: Propane N-Butane

Can Pressure: 40 PST @ 70°F

Flammability: Classified as “extremely flammable”

Flash Point: -4°F

% Solids: 25%

Dry Time: 15 minutes (quicker when temperature exceeds 80°F)

V.O.C.: 48%

Mir Value: 0.61

Gloss: Flat

Chemical Resistance: Fair

Adhesion: Good

Durability: Good

Application Temperature: For best results: 40°-90°F

If the can is subjected to subfreezing temperatures, it should be warmed to the operating temperature range before use to ensure a normal spray pattern. Do not use an open flame to warm the can

Heat Resistance: 250°F

Resin System: V.T. Alkyd

Abrasion Resistance: Good

General Description: a fast drying permanent marking paint applied in an inverted position that is lead free and V.O.C. compliant, and will not wash away.

Suggested Uses:

Utility marking: buried water, gas,
electric and telephone lines.
Golf Courses
Landscaping
Construction sites
Athletic fields
Surveyor's marking
Excavation sites
Mining

Benefits:

Non-clogging
Safe on grass
Fast dry
Produces vivid lines
Meets APWA standard colors
Lead free
V.O.C. Compliant
Converta-Cap allows spraying without
removing and prevents accidental use

MID-AMERICAN RESEARCH CHEMICAL CORP.

P.O. Box 927 * Columbus, Nebraska 68602-0927 * Fax (402)563-1290 * Phone (402) 564-7104