



SAFETY DATA SHEET

Product: MARC 170 STRIPING PAINT – HANDICAP BLUE

Form R04132

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER AND NAME: MARC 170 STRIPING PAINT – HANDICAP BLUE

SDS DATE: 08/23/17

SUPPLIER: Mid-American Research Chemical Corp.

ADDRESS: P. O. Box 927 Columbus, NE 68602-0927

PHONE: 402-564-7104 FAX: 402-563-1290

EMERGENCY PHONE: InfoTrac 1-800-535-5053

E-MAIL: marc@marc1.com WEBSITE: www.marc1.com

RECOMMENDED USE: Line striping

PREPARED BY: MARC

SECTION 2: HAZARDS IDENTIFICATION

CLASSIFICATION: Extremely flammable aerosol. Contains gas under pressure; May explode if heated. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure.



SIGNAL WORD: Danger. **Hazard statements:** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Protect from sunlight. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture of the substances listed below with nonhazardous additions.

<u>CHEMICAL DESCRIPTION</u>	<u>CAS NO.</u>	<u>%WT.</u>
VM&P Naphtha	64742-89-8	20 – 30%
Propane	74-98-6	10 – 15%
Titanium dioxide	13463-67-7	5 – 10%
n-butane	106-97-8	5 – 10%
PM acetate	108-65-6	1 – 3%
Calcium Carbonate	1317-65-3	3 – 8%
Mineral Spirits	64742-47-8	1 – 5%
Xylene(mix)	1330-20-7	1 – 5%

Specific percentages and ingredients may be claimed as a trade secret.

SECTION 4: FIRST AID MEASURES

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects: Dizziness

Indication of any immediate medical attention needed: No further relevant information available.

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: CO₂, extinguishing powder, or water spray. Fight larger fires with water spray.

**SPECIAL FIRE FIGHTING PROCEDURES/
EQUIPMENT:**

A respiratory protective device against the effects of fumes/dust/aerosol. (See Section 8).



SAFETY DATA SHEET

Product: MARC 170 STRIPING PAINT – HANDICAP BLUE

Form R04132

UNUSUAL FIRE AND EXPLOSION HAZARDS: Can form explosive gas-air mixtures. Do not spray on an open flame or other ignition source.

HAZARDOUS DECOMPOSITION PRODUCTS: No dangerous decomposition products known.

SECTION 6: ACCIDENTAL RELEASE MEASURES

**EMERGENCY PROCEDURES/
EQUIPMENT:**

Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol. See Section 8.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP: Same as emergency procedures. Ensure adequate ventilation.

SECTION 7: HANDLING AND STORAGE

**GENERAL HANDLING
STORAGE:**

Use only in well ventilated areas. Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

OTHER PRECAUTIONS: KEEP AWAY FROM CHILDREN! CAREFULLY READ ENTIRE LABEL BEFORE USE!

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with limit values that require monitoring at the workplace:

PROPANE – CAS 74-98-6	
PEL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV (USA)	Refer to Appendix F
N-BUTANE – CAS 106-97-8	
REL (USA)	Long-term value: 1900 mg/m ³ , 800 ppm
TLV (USA)	Short-term value: 2370 mg/m ³ , 1000 ppm
PM Acetate – CAS 108-65-6	
WEEL (USA GHS)	Long-term value: 50 ppm
XYLENE (MIX) – CAS 1330-20-7	
PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 655 mg/m ³ , 150 ppm
	Long-term value: 435 mg/m ³ , 100 ppm
	Short-term value: 651 mg/m ³ , 150 ppm
TLV (USA)	Long-term value: 434 mg/m ³ , 100 ppm
	BEI

Ingredients with biological limit values:

XYLENE (MIX) – CAS 1330-20-7	
BEI (USA)	1.5 g/g creatine Medium: urine Time: end of shift Parameter: Methylhippuric acids

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Wash hands after use. Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Nitrile gloves. Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles.



SAFETY DATA SHEET

Product: MARC 170 STRIPING PAINT – HANDICAP BLUE

Form R04132

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE-	
PHYSICAL STATE/COLOR:	Aerosol/Blue
ODOR:	Aromatic
ODOR THRESHOLD:	Not determined.
SOLUBILITY IN WATER:	Not determined.
MELTING/FREEZING POINT:	Undetermined.
BOILING POINT:	-44°C (-47°F)
pH:	Not Determined
FLASH POINT/METHOD USED:	-19°C (-2°F)
FLAMMABILITY LIMITS (solid, gaseous):	Extremely flammable.
DANGER OF EXPLOSION:	In use, may form flammable/explosive vapor-air mixture.
LOWER EXPLOSION LIMIT:	1.7 Vol %
UPPER EXPLOSION LIMIT:	10.9 Vol %
VAPOR PRESSURE (mmHg):	Not determined.
RELATIVE DENSITY:	Between 0.77 and 0.85 (water equals 1.00)
VAPOR DENSITY:	Not determined.
EVAPORATION RATE:	Not applicable.
PARTITION COEFFICIENT, n-OCTANOL/WATER:	Not determined.
AUTO-IGNITION TEMPERATURE:	Product is not self-igniting.
DECOMPOSITION TEMPERATURE:	Not determined.
VISCOSITY:	Not determined.
VOC CONTENT (less exempt solvents):	48.6%
WATER:	21.7%
SOLIDS CONTENT:	28.6%

SECTION 10: STABILITY AND REACTIVITY

STABILITY & REACTIVITY:	Stable at normal temperatures.
POSSIBILITY OF HAZARDOUS REACTIONS:	No dangerous reactions known.
CONDITIONS TO AVOID:	Do not allow the can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
INCOMPATIBILITY (MATERIAL TO AVOID):	No further relevant information available.
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:	No dangerous decomposition products known.
HAZARDOUS POLYMERIZATION: No	CONDITIONS TO AVOID (POLYMERIZATION): None known.

SECTION 11: TOXICOLOGICAL INFORMATION

LD/LC50 values that are relevant for classification:

TITANIUM DIOXIDE – CAS 13463-67-7

Oral	LD50	>20000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rbt)
Inhalative	LC50/4 h	>6.82 mg/l (rat)

N-BUTANE – CAS 106-97-8

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

PM acetate – CAS 108-65-6

Oral	LD50	8500 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)

XYLENE (MIX) – CAS 1330-20-7

Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
Inhalative	LC50/4 h	6350 mg/l (rat)



SAFETY DATA SHEET

Product: MARC 170 STRIPING PAINT – HANDICAP BLUE

Form R04132

Information on toxicological effects: No data available.
Sensitization: No sensitizing effects known.

CARCINOGENIC CATEGORIES

IARC (International Agency for Research on Cancer)	
TITANIUM OXIDE	CAS 13463-67-7
XYLENE (MIX)	CAS 1330-20-7
NTP (National Toxicology Program)	
None of the ingredients is listed.	
OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

SECTION 12: ECOLOGICAL INFORMATION

AQUATIC TOXICITY: Hazardous for water. Do not empty into drains.
PERSISTENCE AND DEGRADABILITY: The product is degradable after prolonged exposure to natural weathering processes.
BIOACCUMULATIVE POTENTIAL: No further relevant information available.
MOBILITY IN SOIL: No further relevant information available.
OTHER ADVERSE EFFECTS: No further relevant information available.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION (for ground/non-bulk containers)

CONTAINER SIZES(S): 18.0 Ounce Aerosol Can (511 g)
PROPER SHIPPING NAME: PAINT
HAZARD CLASS: None
ID NUMBER: None
PACKING GROUP: -
LABEL STATEMENT: LTD QTY

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listing):

XYLENE (MIX)	CAS 1330-20-7
--------------	---------------

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

TITANIUM DIOXIDE	CAS 13463-67-7
ETHYL BENZENE	CAS 100-41-4

EPA:

XYLENE (MIX)	CAS 1330-20-7
--------------	---------------

SECTION 16: OTHER INFORMATION

HMIS/NFPA Ratings: Health = 1, Flammability = 3, Reactivity = 3. REVISION DATE: 08/23/17

DISCLAIMER: While the information contained herein is believed to be correct, no warranties are made with respect thereto, and all liability from reliance thereon is disclaimed. This product was manufactured in the U.S.A.