



SAFETY DATA SHEET

Product: **MARC 24 ASPHALT SOFTENER**

Form R04132

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER AND NAME: **MARC 24 ASPHALT SOFTENER**

SDS DATE: 10/27/16

SUPPLIER: Mid-American Research Chemical Corp. ADDRESS: P. O. Box 927 Columbus, NE 68602-0927
PHONE: 402-564-7104 FAX: 403-563-1290
EMERGENCY PHONE: InfoTrac 1-800-535-5053
E-MAIL: marc@marc1.com WEBSITE: www.marc1.com

RECOMMENDED USE: Asphalt softener.

PREPARED BY: MARC

SECTION 2: HAZARDS IDENTIFICATION

OSHA/HCS STATUE: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE: **FLAMMABLE LIQUIDS - Category 2**
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/EYE IRRITATION- Category 2A
TOXIC TO REPRODUCTION (Fertility) – Category 2
TOXIC TO REPRODUCTION (Unborn child) – Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [respiratory tract irritation] – Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) – Category 2
ASPIRATION HAZARD - Category 1

GHS Label elements:
HAZARD PICTOGRAMS



SIGNAL WORD: **DANGER!**

HAZARD STATEMENTS: Highly flammable liquid and vapor.
Causes serious eye irritation.
Causes skin irritation.
Suspected of damaging fertility or the unborn child.
May be fatal if swallowed and enters airways.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS

GENERAL: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

PREVENTION: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Keep away from heat, sparks, open flames and hot surfaces. – No Smoking. Use explosion-proof electrical, ventilating, and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. do not breathe vapor. Wash hands thoroughly after handling.

RESPONSE: Get medical attention if you feel unwell. If exposed or concerned: Get medical attention. **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. **IF SWALLOWED:** Immediately call a POISON CENTER or physician. **DO NOT INDUCE VOMITING! IF ON SKIN (or hair):** Take off immediately all contaminated clothing. Rinse skin with water or shower. **IF ON SKIN:** Wash with plenty of soap and water. Take off contaminated clothing. If skin irritation occurs: Get medical attention. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.



SAFETY DATA SHEET

Product: **MARC 24 ASPHALT SOFTER**

Form R04132

STORAGE: Store locked up. Store in a well-ventilated place. Keep cool.

DISPOSAL: Dispose of contents and container in accordance with all local, regional, national and international regulations.

HAZARDS NOT OTHERWISE CLASSIFIED: None known.

POTENTIAL HEALTH EFFECTS: See Section 11 for more information.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCE/MIXTURE: Mixture

OTHER MEANS OF IDENTIFICATION: Not available.

INGREDIENT NAME	CAS NUMBER	%
Toluene	108-88-3	75%
Ethyl 3-ethoxypropionate	763-69-9	25%

Occupational exposure limits, if available, are listed in Section 8.

Specific percentages may be claimed as a trade secret.

SECTION 4: FIRST AID MEASURES

EYES: Flush immediately with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

SKIN: Flush contaminated skin with plenty of water. Remove contaminated clothing, shoes, and leather goods. Continue to rinse at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

INGESTION: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. **DO NOT INDUCE VOMITING!** If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

INHALATION: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

MOST IMPORTANT SYMPTOMS/EFFECTS.

ACUTE AND DELAYED

POTENTIAL ACUTE HEALTH EFFECTS:

EYE CONTACT: Causes serious eye irritation.

INHALATION: May cause respiratory irritation.

SKIN CONTACT: Causes skin irritation.

INGESTION: May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.



SAFETY DATA SHEET

Product: **MARC 24 ASPHALT SOFTER**

Form R04132

OVER-EXPOSURE SIGNS/SYMPTOMS:

- EYE CONTACT:** Adverse symptoms may include the following: pain or irritation, watering, redness.
- INHALATION:** Adverse symptoms may include the following: respiratory tract irritation, coughing, reduced fetal weight, increase in fetal deaths, skeletal malformations.
- SKIN CONTACT:** Adverse symptoms may include the following: irritation, redness, reduced fetal weight, increase in fetal deaths, skeletal malformations.
- INGESTION:** Adverse symptoms may include the following: nausea or vomiting, reduced fetal weight, increase in fetal deaths, skeletal malformations.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED, IF NECESSARY:

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

SPECIFIC TREATMENTS: No specific treatment.

PROTECTION OF FIRST-AIDERS: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

SECTION 5: FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: CO₂, Dry Chemical, Water spray (fog), or foam.

UNSUITABLE EXTINGUISHING MEDIA: Do not use water jet.

SPECIAL FIRE FIGHTING PROCEDURES: Promptly isolate the scent by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Highly flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard

HAZARDOUS THERMAL DECOMPOSITION PRODUCTS: May include the following materials: carbon monoxide, carbon dioxide.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

FOR NON-EMERGENCY PERSONNEL: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

FOR EMERGENCY RESPONDERS: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".



SAFETY DATA SHEET

Product: **MARC 24 ASPHALT SOFTER**

Form R04132

ENVIRONMENTAL PRECAUTIONS: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).-

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP:

SMALL SPILL: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

LARGE SPILL: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach releases from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. NOTE: See Section 1 for Emergency contact information and Section 13 for Waste Disposal.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

PROTECTIVE MEASURES: Put on appropriate personal protective equipment (see Section 8). Avoid exposure – obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

ADVICE ON GENERAL

OCCUPATIONAL HYGIENE: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drink and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

OTHER PRECAUTIONS: **KEEP AWAY FROM CHILDREN!**



SAFETY DATA SHEET

Product: **MARC 24 ASPHALT SOFTER**

Form R04132

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

OCCUPATIONAL EXPOSURE LIMITS

Toluene

ACGIH TLV (United States, 2007).

TWA: 20 ppm

APPROPRIATE ENGINEERING CONTROLS/ VENTILATION:

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental Exposure Controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

INDIVIDUAL PROTECTION MEASURES:

EYE/FACE PROTECTION:

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

SKIN PROTECTION:

HAND PROTECTION:

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Ensure that eyewash stations and safety showers are close to the workstation location.

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

RESPIRATORY PROTECTION:

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

WORK HYGIENIC PRACTICES:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.



SAFETY DATA SHEET

Product: **MARC 24 ASPHALT SOFTER**

Form R04132

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE-	
PHYSICAL STATE:	Liquid.
COLOR:	Colorless.
ODOR:	Organic chemicals.
ODOR THRESHOLD:	Not available.
pH:	Not available.
MELTING POINT:	May start to solidify at the following temperature: -94.5°C (-138.1°F). This is based on data for the following ingredient: Toluene
BOILING POINT:	Lowest known value: 110.6°C (231.1°F) (Toluene). Weighted average: 124.2°C (255.6°F)
FLASH POINT/METHOD USED:	Lowest known value: Open cup: 12.78°C (55°F). (Cleveland). (Toluene).
BURNING TIME:	Not applicable.
BURNING RATE:	Not applicable.
EVAPORATION RATE:	Highest known value: 2 (Toluene) Weighted average: 1.53 compared with Butyl acetate.
FLAMMABILITY (solid, gas):	Not available.
UPPER & LOWER Explosive (flammable) Limits:	Greatest known range: Lower: 1.2% Upper: 7.1% (Toluene)
VAPOR PRESSURE (mmHg):	Highest known value: 2.9 kPa (21.9 mm Hg) (@ 20°C) (Toluene). Weighted average: 23 kPa (16.73 mm Hg) (@ 20°C)
VAPOR DENSITY (AIR = 1):	Highest known value: 5 (air=1) (Ethyl 3-ethoxypropionate). Weighted average: 3.61 (Air = 1)
RELATIVE DENSITY:	Weighted average: 0.89 (water=1)
SOLUBILITY:	Easily soluble in the following materials: methanol, diethyl ether. Soluble in the following materials: n-octanol, acetone. Insoluble in the following materials: cold water, hot water.
SOLUBILITY IN WATER:	Not available.
PARTITION COEFFICIENT, n-OCTANOL/WATER:	Not available.
AUTO-IGNITION TEMPERATURE:	Lowest known value: 480 °C (896°F) (Toluene).
DECOMPOSITION TEMPERATURE:	Not available.
SADT:	Not available.
VISCOSITY:	Not available.

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY:	No specific test data related to reactivity available for this product or its ingredients.
CHEMICAL STABILITY:	The product is stable.
POSSIBILITY OF HAZARDOUS REACTIONS:	Under normal conditions of storage and use, hazardous reactions will not occur.
CONDITIONS TO AVOID:	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
INCOMPATIBILITY (MATERIAL TO AVOID):	Reactive or incompatible with the following materials: oxidizing materials.
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
HAZARDOUS POLYMERIZATION:	No
CONDITIONS TO AVOID (POLYMERIZATION):	NA



SAFETY DATA SHEET

Product: **MARC 24 ASPHALT SOFTER**

Form R04132

SECTION 11: TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY

PRODUCT/INGREDIENT NAME	RESULT	SPECIES	DOSE	EXPOSURE
Toluene	LC50 Inhalation Gas.	Rat	>5000ppm	1 hour
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-

IRRITATION/CORROSION: Not available

SENSITIZATION: Not available

MUTAGENICITY: Not available.

CARCINOGENICITY: Not available

CLASSIFICATION

PRODUCT/INGREDIENT NAME	OSHA	IARC	NTP
Toluene	-	4	-

REPRODUCTIVE TOXICITY: Not available

TERATOGENICITY: Not available

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE): Not available

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE): Not available

ASPIRATION HAZARD: Not available.

INFORMATION ON THE LIKELY ROUTES OF EXPOSURE: Not available

POTENTIAL ACUTE HEALTH EFFECTS

EYE CONTACT: Causes serious eye irritation.

INHALATION: May cause respiratory irritation.

SKIN CONTACT: Causes skin irritation.

INGESTION: May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:

EYE CONTACT: Adverse symptoms may include the following: pain or irritation, watering, redness.

INHALATION: Adverse symptoms may include the following: respiratory tract irritation, coughing, reduced fetal weight, increase in fetal deaths, skeletal malformations.

SKIN CONTACT: Adverse symptoms may include the following: irritation, redness, reduced fetal weight, increase in fetal deaths, skeletal malformations.

INGESTION: Adverse symptoms may include the following: nausea or vomiting, reduced fetal weight, increase in fetal deaths, skeletal malformations.



SAFETY DATA SHEET

Product: **MARC 24 ASPHALT SOFTER**

Form R04132

DELAYED AND IMMEDIATE EFFECTS AND ALSO CHRONIC EFFECTS FROM SHORT AND LONG TERM EXPOSURE:

SHORT TERM EXPOSURE

Potential immediate effects: Not available.

Potential delayed effects: Not available.

LONG TERM EXPOSURE

Potential immediate effects: Not available.

Potential delayed effects: Not available.

POTENTIAL CHRONIC HEALTH EFFECTS: Not available.

GENERAL: May cause damage to organs through prolonged or repeated exposure.
CARCINOGENICITY: No known significant effects or critical hazards.
MUTAGENICITY: No known significant effects or critical hazards.
TERATOGENICITY: Suspected of damaging the unborn child.
DEVELOPMENTAL EFFECTS: No known significant effects or critical hazards.
FERTILITY EFFECTS: Suspected of damaging fertility.

NUMERICAL MEASURES OF TOXICITY

ACUTE TOXICITY ESTIMATES: Not available.

SECTION 12: ECOLOGICAL INFORMATION

TOXICITY: Not available.

PERSISTENCE and DEGRADABILITY: Not available.

BIOACCUMULATIVE POTENTIAL: Not available.

MOBILITY IN SOIL: Not available.
Soil/water partition
Coefficient (Koc)

OTHER ADVERSE EFFECTS: No known significant effects or critical hazards.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



SAFETY DATA SHEET

Product: **MARC 24 ASPHALT SOFTER**

Form R04132

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION (for ground/non-bulk containers)

CONTAINER SIZES(S): Bulk, 5 Gallon
PROPER SHIPPING NAME: COMPOUND CLEANING LIQUID (CONTAINS TOLUENE)
HAZARD CLASS: 3
ID NUMBER: NA1993
PACKING GROUP: II
LABEL STATEMENT: FLAMMABLE LIQUID

CONTAINER SIZES(S): Quarts, Pints
PROPER SHIPPING NAME: COMPOUND CLEANING LIQUID
HAZARD CLASS: NONE
ID NUMBER: NONE
PACKING GROUP: NONE
LABEL STATEMENT: LTD QTY SYMBOL

SPECIAL PRECAUTIONS FOR USER: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA 8 (a) CDR Exempt (Partial exemption: Not determined.

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Air Act Section 112: Listed
(b) Hazardous Air Pollutants (HAPS)

Clean Air Act Section 602: Not Listed
Class I Substances

Clean Air Act Section 602: Not Listed
Class II Substances

DEA List I Chemicals: Not Listed
(Precursor Chemicals)

DEA List II Chemicals: Not Listed
(Essential Chemicals)

SARA 302/304

Composition/Information on ingredients

No products were found.

SARA 304 RQ: Not applicable.

SARA 311/312

Classification: Fire Hazard
Immediate (acute) health hazard
Delayed (chronic) health hazard



SAFETY DATA SHEET

Product: **MARC 24 ASPHALT SOFTER**

Form R04132

SARA 313

	PRODUCT NAME	CAS NUMBER	%
Form R – reporting requirements	Toluene	108-88-3	75

Sara 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

California Prop 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

INGREDIENT NAME	CANCER	REPRODUCTIVE	NO SIGNIFICANT RISK LEVEL	MAXIMUM ACCEPTABLE DOSAGE LEVEL
Toluene	No	Yes	No	No

SECTION 16: OTHER INFORMATION

HMIS/NFPA Ratings: Health = 2
Flammability = 3
Reactivity = 0
Other = -
Protection = -

REVISION DATE: 10/27/16

N/A = Not Applicable, N/D = Not Determined, N/E = Not Established

DISCLAIMER: While the information contained herein is believed to be correct, no warranties are made with respect thereto, and all liability from reliance thereon is disclaimed.