



SAFETY DATA SHEET

Product: MARC 264 SQUEAKY CLEAN

Form R04132

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER AND NAME: MARC 264 SQUEAKY CLEAN

SDS DATE: 07/07/16

SUPPLIER: Mid-American Research Chemical Corp. ADDRESS: P. O. Box 927 Columbus, NE 68602-0927
PHONE: 402-564-7104 FAX: 403-563-1290
EMERGENCY PHONE: InfoTrac 1-800-535-5053
E-MAIL: marc@marc1.com WEBSITE: www.marc1.com

RECOMMENDED USE: Cleaner for Wood Floors.

PREPARED BY: MARC

SECTION 2: HAZARDS IDENTIFICATION

CLASSIFICATION: This material is hazardous under the criterion of the Federal OSHA Hazard Communication standard 29 CFR 1910.1200.

Flammable liquids – Category 2
Eye irritation – Category 2A
Specific target organ toxicity – single exposure – Category 3



SIGNAL WORD AND PRECAUTIONARY STATEMENTS: **DANGER:** Flammable liquid and vapor. Causes eye irritation. May cause skin irritation. May be harmful if swallowed. Keep away from heat, sparks, open flames and other ignition sources. No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Wear protective gloves and eye protection. Avoid breathing vapors or mists. Wash skin thoroughly after handling. Use only in a well-ventilated area. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If irritation persists, seek medical attention. **IF ON SKIN:** Immediately take off all contaminated clothing. Rinse skin with water. If skin irritation or rash occurs, seek medical advice. Wash contaminated clothing before reuse. **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. **IF SWALLOWED:** Call a **POISON CENTER** or seek medical advice if you feel unwell. **IN CASE OF FIRE:** Use dry sand, dry chemical or alcohol-resistant foam for extinction. Store locked up in a cool, dry, well-ventilated area. Dispose of contents in accordance with all applicable local, regional and national regulations.

OTHER HAZARDS: No data available.

POTENTIAL HEALTH EFFECTS: See Section 11 for more information.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>PERCENT</u>
Isopropanol	67-63-0	12% - 20%
Nonylphenol Ethoxylate	127087-81-0	5% - 8%

Percentage of composition has been withheld as a trade secret.

SECTION 4: FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, after first 5 minutes, if present and easy to do. Continue rinsing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

SKIN: Take off immediately all contaminated clothing. Rinse skin with plenty of water. If skin irritation or rash occurs, seek medical advice. Wash contaminated clothing before reuse.



SAFETY DATA SHEET

Product: MARC 264 SQUEAKY CLEAN

Form R04132

INGESTION: **DO NOT INDUCE VOMITING!** Call a physician and/or transport to emergency facility immediately. Show this container or label.

INHALATION: Move person to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

MOST IMPORTANT SYMPTOMS/ EFFECTS, ACUTE & DELAYED: Aside from the information found under **SECTION 4: FIRST AID MEASURES, and INDICATION OF IMMEDIATE MEDICAL ATTENTION and SPECIAL TREATMENT NEEDED** (below), any additional important symptoms and effects are described in **SECTION 11: TOXICOLOGY INFORMATION**.

INDICATION OF IMMEDIATE MEDICAL ATTENTION & SPECIAL TREATMENT NEEDED:

NOTES TO PHYSICIAN: Maintain adequate ventilation and oxygenation of the patient. Because rapid absorption may occur through the lungs if aspirated and cause systemic effects, the decision of whether to induce vomiting or not should be made by a physician. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Hemodialysis may be of benefit if substantial amounts have been ingested and the patient is showing signs of intoxication. Consider hemodialysis for patients with persistent hypotension or coma unresponsive to standard therapy (isopropanol levels >400 – 500 mg/dl). (Goldfrank 1998, King et al, 1970). No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Skin contact may aggravate preexisting dermatitis.

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

UNSUITABLE EXTINGUISHING MEDIA: Do not use direct water stream. Straight or direct water streams may not be effective to extinguish fire.

SPECIAL FIRE FIGHTING PROCEDURES
FIRE-FIGHTING EQUIPMENT: Keep people away. Isolate fire and deny unnecessary entry. Stay upwind. Keep out of low areas where gases (fumes) can accumulate. Water may not be effective in extinguishing fire. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed.

Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves).

UNUSUAL FIRE AND EXPLOSION HAZARDS: Container may vent and/or rupture due to fire. When product is stored in closed containers, a flammable atmosphere can develop. Electrically ground and bond all equipment. Flammable mixtures of this product are readily ignited even by static discharge. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Flammable mixtures may exist within the vapor space of containers at room temperature. Flammable concentrations of vapor can accumulate at temperatures above flash point; see **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**.

HAZARDOUS DECOMPOSITION PRODUCTS: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide, Carbon dioxide.



SAFETY DATA SHEET
Product: MARC 264 SQUEAKY CLEAN

Form R04132

SECTION 6: ACCIDENTAL RELEASE MEASURES

**EMERGENCY PROCEDURES/
PERSONAL PRECAUTIONS:**

Ventilate area of leak or spill. No smoking in area. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Vapor explosion hazard. Keep out of sewers.

LARGE SPILLS: Warn public of downwind explosion hazard. Check area with combustible gas detector before reentering area. Ground and bond all containers and handling equipment. Use appropriate safety equipment. Refer to **SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION**.

PROTECTIVE EQUIPMENT:

Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves).

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP: Contain spilled material if possible. Ground and bond all containers and handling equipment. Pump with explosion-proof equipment. Pump with explosion-proof equipment. If available, use foam to smother or suppress. Collect in suitable and properly labeled containers.

ENVIRONMENTAL PRECAUTIONS: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater.

SECTION 7: HANDLING AND STORAGE

**PRECAUTIONS FOR
SAFE HANDLING/
STORAGE:**

Keep away from heat, sparks and flame. Avoid contact with eyes. Avoid breathing vapor. Wash thoroughly after handling. Keep container closed. Use only with adequate ventilation. No smoking, open flames or sources of ignition in handling and storage area. Use of non-sparking or explosion-proof equipment may be necessary.

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN! READ LABEL CAREFULLY!

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS:

EXPOSURE LIMITS ARE LISTED BELOW, IF THEY EXIST.

COMPONENT	REGULAITON	TYPE OF LISTING	VALUE/NOTATION
Isopropanol	ACGIH	TWA	200 ppm

**APPROPRIATE ENGINEERING
CONTROLS/VENTILATION:**

Local exhaust ventilation.

RESPIRATORY PROTECTION: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus. In confined or poorly ventilated areas, use an approved self-contained breathing apparatus or positive pressure-air line with auxiliary self-contained air supply.

EYE/FACE PROTECTION: Use chemical goggles.

SKIN PROTECTION/PROTECTIVE GLOVES: Wear gloves-chemically resistant.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Wear clean, body-covering clothing. Suitable emergency eye wash facility should be available.

WORK HYGIENIC PRACTICES: When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.



SAFETY DATA SHEET

Product: MARC 264 SQUEAKY CLEAN

Form R04132

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	
PHYSICAL STATE:	Liquid.
COLOR:	Orange
ODOR:	Alcohol
ODOR THRESHOLD:	No test data available.
pH:	7-8
MELTING POINT/RANGE:	Not applicable to liquids.
FREEZING POINT:	N/D
BOILING POINT (760 mmHg):	180° F
FLASH POINT/METHOD USED:	>100° F Tag Closed Cup ASTM D56
EVAPORATION RATE:	N/D
FLAMMABILITY (solid, gas):	Flammable liquid.
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:	
Explosive limit - lower:	N/D
Explosive limit - upper:	N/D
VAPOR PRESSURE (mmHg):	N/D
RELATIVE VAPOR DENSITY (AIR = 1):	2.1 Literature
RELATIVE DENSITY (WATER = 1):	0.97
SOLUBILITY IN WATER:	100%
PARTITION COEFFICIENT, n-OCTANOL/WATER:	N/D
AUTO-IGNITION TEMPERATURE:	N/D
DECOMPOSITION TEMPERATURE:	No test data available.
KINEMATIC VISCOSITY:	No test data available.
EXPLOSIVE PROPERTIES:	Not explosive
OXIDIZING PROPERTIES:	No

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY: No data available.

CHEMICAL STABILITY: Thermally stable at typical use temperatures.

POSSIBILITY OF HAZARDOUS

REACTIONS: Polymerization will not occur.

CONDITIONS TO AVOID: Exposure to elevated temperatures can cause product to decompose. Avoid static discharge.

INCOMPATIBILITY (MATERIAL TO AVOID): Aldehydes. Halogenated organics. Halogens. Strong acids. Strong oxidizers.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Decomposition products depend upon temperature, air supply and the presence of other materials.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID (POLYMERIZATION): See above.



SAFETY DATA SHEET

Product: MARC 264 SQUEAKY CLEAN

Form R04132

SECTION 11: TOXICOLOGICAL INFORMATION

Toxicological information on this product or its components appear in this section when such data is available.

ACUTE TOXICITY

ISOPROPANOL

ACUTE ORAL TOXICITY:

Low toxicity if swallowed.

LD50, Rat, 5,840 mg/kg OECD 401 or equivalent
Lethal Dose, Humans, 100 ml Estimated.

ACUTE DERMAL TOXICITY:

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

LD50, Rabbit, > 12,800 mg/kg

NONYLPHENOL ETHOXYLATE:

LD50 Oral Rat 3310 mg/kg,
LD50 Dermal Rabbit > 2000 mg/kg
LD50, Rat, male and female, 6 Hour, vapor, >10000 ppm

Skin corrosion/irritation:

Prolonged exposure not likely to cause significant skin irritation.
May cause drying and flaking of the skin.

Serious eye damage/eye irritation:

May cause pain disproportionate to the level of irritation to eye tissues.
May cause moderate eye irritation.
May cause moderate corneal injury.

Specific target organ toxicity- Single exposure:

May cause drowsiness and dizziness. Route of exposure: Ingestion.
Target Organs: Central nervous system.

Specific target organ toxicity- Repeated exposure:

In animals, effects have been reported on the following organs: Kidney, Liver.

Carcinogenicity:

Does not cause cancer in lab mice.

Aspiration Hazard:

May be harmful if swallowed and enters airways.

SECTION 12: ECOLOGICAL INFORMATION

TOXICITY

ISOPROPANOL

ACUTE TOXICITY TO FISH:

(LC50/EC50/EL50/LL50>100 mg/L in the most sensitive species tested).

LC50, Pimephales promelas (fathead minnow). Flow-through test, 96 Hour, 9,640 mg/l,
OECD Test Guideline 203 or Equivalent.



SAFETY DATA SHEET

Product: MARC 264 SQUEAKY CLEAN

Form R04132

ACUTE TOXICITY TO AQUATIC INVERTEBRATES: LC50, Daphnia magna (Water flea), static test, 24 Hour, > 1,000 mg/l, OECD Test Guideline 202 or Equivalent

ACUTE TOXICITY TO ALGAE/AQUATIC PLANTS: NOEC, alga Scenedesmus sp., static test, 7 d, Growth inhibition (cell density reduction), 1,800 mg/l

ErC50, alga Scenedesmus sp., static test, 72 Hour, Growth rate inhibition, > 1,000 mg/l

CHRONIC AQUATIC TOXICITY

CHRONIC TOXICITY TO AQUATIC INVERTEBRATES: NOEC, Daphnia magna (Water flea), semi-static test, 21 d, 30 mg/l

NONYLPHENOL ETHOXYLATE: Acute LC50 Fish: 1 to 10 mg/l – 96 Hours

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations.

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION (for ground/non-bulk containers)

CONTAINER SIZE(S):	PAILS, GALLONS
PROPER SHIPPING NAME:	COMPOUND, CLEANING, LIQUID
HAZARD CLASS:	N/A
ID NUMBER:	NONE
PACKING GROUP:	NONE
LABEL STATEMENT:	NONE

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

OSHA HAZARD COMMUNICATION STANDARD:

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

UNITED STATES TSCA INVENTORY (TSCA):

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 TITLE III (Emergency Planning and Community Right-To-Know Act of 1986) Sections 311 and 312:

Fire Hazard
Acute Health Hazard
Chronic Health Hazard

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 TITLE III (Emergency Planning and Community Right-To-Know Act of 1986) Sections 313:

COMPONENTS
ISOPROPANOL

CASRN
67-63-0



SAFETY DATA SHEET

Product: MARC 264 SQUEAKY CLEAN

Form R04132

COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT OF 1980 (CERCLA) SECTION 103:

This product contains the following substances which are subject to CERCLA Section 103 reporting requirements and which are listed in 40 CFR 302.4.

SECTION 16: OTHER INFORMATION

HMIS/NFPA Ratings: Health = 0
Flammability = 2
Reactivity = 0
Other = -
Protection = -

LEGEND

ACGIH	USA. ACGHI Threshold Limit Values (TLV)
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) – Table Z-1 Limits for Air Contaminants
STEL	Short-term exposure limit
TWA	8-hour, time-weighted average

REVISION DATE: 07/07/16

N/A = Not Applicable, N/D = Not Determined, N/E = Not Established

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DISCLAIMER: MID-AMERICAN RESEARCH CHEMICAL CORPORATION urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer specific SDSs, we are not and cannot be responsible for SDSs obtained from any source other than ourselves. If you have obtained an SDS from another source or if you are not sure that the SDS you have is current, please contact us for the most current version.